



KONGSBERG

# INTERFACE SPECIFICATIONS

Simrad Sonar Systems





PUBLIC



KONGSBERG

# ***Simrad***

## ***Sonar systems***

### ***Interface specifications***

The purpose of this manual is to provide the descriptions required to communicate effectively with the sonar system.

*Caution* \_\_\_\_\_

*You must never permit the sonar system to transmit (ping) when the ship is in a dry dock. The transducer can be damaged if it transmits in the open air.*

---

Additional end-user documents related to the sonar system can be found on our website. This includes publications that are translated into other languages. Selected publications are also provided in IETM (*Interactive Electronic Technical Manual*) formats.

- <https://www.kongsberg.com/fisherysonar>

**SIMRAD**  
By KONGSBERG

## **Document information**

- **Product:** Simrad sonar
- **Document:** Interface specifications
- **Document part number:** 110-0007577
- **Document ISBN number:** 978-82-8066-239-2
- **Revision:** C
- **Date of issue:** 12 June 2023

## **Significant changes to the product or this publication**

- ☛ [About this manual, page 7](#)

## **Copyright**

*The information contained in this document remains the sole property of Kongsberg Maritime AS. No part of this document may be copied or reproduced in any form or by any means, and the information contained within it is not to be communicated to a third party, without the prior written consent of Kongsberg Maritime AS.*

## **Warning**

*The equipment to which this manual applies must only be used for the purpose for which it was designed. Improper use or maintenance may cause damage to the equipment and/or injury to personnel. You must be familiar with the contents of the appropriate manuals before attempting to operate or work on the equipment.*

*Kongsberg Maritime disclaims any responsibility for damage or injury caused by improper installation, use or maintenance of the equipment.*

## **Disclaimer**

*Kongsberg Maritime AS endeavours to ensure that all information in this document is correct and fairly stated, but does not accept liability for any errors or omissions.*

## **Support information**

If you require maintenance or repair, contact your local dealer. You can also contact us using the following address: [simrad.support@simrad.com](mailto:simrad.support@simrad.com). If you need information about our other products, visit <https://www.kongsberg.com/simrad>. On this website you will also find a list of our dealers and distributors.

# Table of contents

<b>ABOUT THIS MANUAL .....</b>	<b>7</b>
<b>SUPPORT INFORMATION .....</b>	<b>9</b>
<b>SUPPORTED DATAGRAM FORMATS .....</b>	<b>12</b>
Inputs .....	13
Supported datagram formats for annotation data .....	13
Supported datagram formats for external depth input.....	14
Supported datagram formats for GPS (position) information .....	14
Supported datagram formats for heading and gyro information .....	15
Supported datagram formats for trawl information.....	16
Supported datagram formats for catch monitoring information.....	18
Supported datagram formats for sound speed sensors .....	18
Supported datagram formats for speed log information.....	19
Supported datagram formats for temperature information.....	20
Supported datagram formats for wind information .....	20
Supported datagram formats for external objects.....	21
Supported datagram formats for palette control .....	21
Supported datagram formats for motion information.....	22
Outputs .....	23
Supported datagram formats for target marker outputs.....	23
<b>DATAGRAM FORMATS .....</b>	<b>24</b>
About NMEA and standard datagram formats .....	25
About the NMEA datagram formats .....	25
NMEA .....	26
NMEA sentence structure .....	26
Standard NMEA 0183 communication parameters.....	27
NMEA datagram formats.....	28
NMEA CUR datagram format .....	28
NMEA DBS datagram format.....	30
NMEA DBT datagram format.....	30
NMEA DDC datagram format .....	31
NMEA DPT datagram format .....	32
NMEA GGA datagram format .....	33
NMEA GGK datagram format .....	34
NMEA GLL datagram format .....	35
NMEA HDG datagram format .....	35
NMEA HDM datagram format .....	36
NMEA HDT datagram format .....	37

---

NMEA MTW datagram format .....	37
NMEA MWD datagram format .....	38
NMEA MWV datagram format .....	38
NMEA RMC datagram format .....	39
NMEA THS datagram format .....	40
NMEA TLL datagram format .....	40
NMEA VBW datagram format .....	41
NMEA VHW datagram format .....	42
NMEA VTG datagram format .....	43
NMEA VWR datagram format .....	44
NMEA ZDA datagram format .....	44
Proprietary datagram formats .....	46
ATS Annotation datagram format .....	46
Simrad PSIMP,C datagram format .....	47
Simrad PSIMP,D datagram format .....	49
Simrad PSIMP,F datagram format .....	51
Simrad DAD datagram format .....	52
Simrad DBS datagram format .....	52
Simrad GLL datagram format .....	53
Simrad HB2 datagram format .....	53
Simrad HFB datagram format .....	54
Simrad MTW datagram format .....	55
Simrad TDS datagram format .....	55
Simrad TFI datagram format .....	56
Simrad TPC datagram format .....	56
Simrad TPR datagram format .....	57
Simrad TPT datagram format .....	58
Simrad TS2 datagram format .....	59
Simrad TTS datagram format .....	59
Simrad MDS datagram format .....	60
Simrad TPP datagram format .....	61
Kongsberg EM Attitude 3000 datagram format .....	62
KM Binary datagram format .....	64
Third-party datagram formats .....	67
AML Sound speed datagram format .....	67
Trimble PTNL,GGK datagram format .....	69
Furuno GPhve datagram format .....	70
Furuno GPatt datagram format .....	71
Hemisphere GNSS GPHEV datagram format .....	72
Teledyne TSS1 datagram format .....	72

Serpe BSC datagram format.....	74
Ryokusei RBY datagram format .....	75
<b>FILE FORMATS.....</b>	<b>77</b>
NetCDF file format .....	78



# About this manual

The purpose of this manual is to provide the descriptions required to communicate effectively with the sonar system.

## Target audience

This manual is intended for users that need to set up communication between the sonar system and peripheral systems and/or sensors. Due to the nature of the descriptions and the level of detail provided by this publication, it is well suited for those who are - or wish to be - expert users.

This manual is a reference book, and as such it is *not* intended for sequential reading. Use the table of content, the index, the search functionality as well as the interactive links to seek out the information you need when you need it.

A good understanding of system functions and controls is essential to fully take advantage of the functionality provided.

## Software version

This publication was created for the following software version: N/A.

## Online information

All end-user manuals provided for operation and installation of your sonar system can be downloaded from our website. This includes publications that are translated into other languages. Selected publications are also provided in IETM (*Interactive Electronic Technical Manual*) formats. Our website also provides information about other products from Kongsberg Maritime.

- <https://www.kongsberg.com/fisherysonar>

## License information

To obtain a license, contact your local dealer.

## Registered trademarks

Observe the registered trademarks that apply.

Simrad®, SIMRAD® and the Simrad® logo are either registered trademarks, or trademarks of Kongsberg Maritime AS in Norway and other countries.

Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.

### **Significant changes to the product or this publication**

We have implemented the following significant changes in this publication:

#### **NetCDF file format**

The requirement for data storage is from 15 to 50 Gb per hour, depending on your operating modes and settings.

#### **We want your feedback**

We always want to improve our products. We also want our end-user documentation to be comprehensive and relevant. You can help. Please provide comments, suggestions or constructive criticism to any of our support offices.

# Support information

If you need technical support for your sonar system you must contact your local dealer, or one of our support offices. A list of all our offices and dealers is available on our website. You can also contact our main support office in Norway.

## Norway (main office)

- **Company name:** Kongsberg Maritime AS / Simrad
- **Address:** Strandpromenaden 50, N3190 Horten, Norway
- **Telephone:** +47 33 03 40 00
- **Telefax:** +47 33 04 29 87
- **Website :**[www.kongsberg.com/simrad](http://www.kongsberg.com/simrad)
- **Email address:** [simrad.support@simrad.com](mailto:simrad.support@simrad.com)

## Spain

- **Company name:** Kongsberg Maritime Spain S.L.U
- **Address:** Partida Atalayes 20, 03570 Villajoyosa, Spain
- **Telephone:** +34 966 810 149
- **Telefax:** +34 966 852 304
- **Website :**[www.kongsberg.com/simrad](http://www.kongsberg.com/simrad)
- **Email address:** [simrad.spain@simrad.com](mailto:simrad.spain@simrad.com)

## France

- **Company name:** Simrad France
- **Address:** 5 rue de Men Meur, 29730 Guilvinec, France
- **Telephone:** +33 298 582 388
- **Telefax:** +33 298 582 388
- **Website :**[www.kongsberg.com/simrad](http://www.kongsberg.com/simrad)
- **Email address:** [simrad.france@simrad.com](mailto:simrad.france@simrad.com)

## USA

- **Company name:** Kongsberg Underwater Technology LLC (KUTL) / Simrad Fisheries
- **Address:** 19210 33rd Ave W, Suite A, Lynnwood, WA 98036, USA
- **Telephone:** +1 425 712 1136
- **Telefax:** +1 425 712 1193
- **Website :**[www.kongsberg.com/simrad](http://www.kongsberg.com/simrad)
- **Email address:** [fish.usa.support@simrad.com](mailto:fish.usa.support@simrad.com)

## Canada

- **Company name:** Kongsberg Mesotech Ltd.
- **Address:** 1598 Kebet Way, Port Coquitlam, BC, V3C 5M5, Canada
- **Telephone:** +1 604 464 8144
- **Telefax:** +1 604 941 5423
- **Website :**[www.kongsberg.com/simrad](http://www.kongsberg.com/simrad)
- **Email address:** [simrad.canada@simrad.com](mailto:simrad.canada@simrad.com)

## Malaysia

- **Company name:** Kongsberg Maritime Malaysia Sdn. Bhd
- **Address:** Unit 27-5 Signature Offices, The Boulevard, Mid Valley City, Lingkaran Syed Putra, 59200 Kuala Lumpur, Malaysia
- **Telephone:** +65 6411 7488
- **Telefax:** +60 3 2201 3359
- **Website :**[www.kongsberg.com/simrad](http://www.kongsberg.com/simrad)
- **Email address:** [simrad.asia@simrad.com](mailto:simrad.asia@simrad.com)

## Korea

- **Company name:** Kongsberg Maritime Korea Ltd
- **Address:** #1101 Harbor Tower, 113-1, Nampodong 6-Ga, Jung-Gu, Busan 600-046, Korea
- **Telephone:** +82 51 242 9933
- **Telefax:** +82 51 242 9934
- **Website :**[www.kongsberg.com/simrad](http://www.kongsberg.com/simrad)
- **Email address:** [simrad.korea@simrad.com](mailto:simrad.korea@simrad.com)

## China

- **Company name:** Kongsberg Maritime China Ltd
- **Address:** 555 Chuanqiao Road, China (Shanghai) Pilot Free Trade Zone, 201206, China

- **Telephone:** +86 21 3127 9888
- **Telefax:** +86 21 3127 9555
- **Website :**[www.kongsberg.com/simrad](http://www.kongsberg.com/simrad)
- **Email address:** [simrad.china@simrad.com](mailto:simrad.china@simrad.com)

# Supported datagram formats

## Topics

[Inputs, page 13](#)

[Outputs, page 23](#)

# Inputs

## Topics

- [Supported datagram formats for annotation data, page 13](#)
- [Supported datagram formats for external depth input, page 14](#)
- [Supported datagram formats for GPS \(position\) information, page 14](#)
- [Supported datagram formats for heading and gyro information, page 15](#)
- [Supported datagram formats for trawl information, page 16](#)
- [Supported datagram formats for catch monitoring information, page 18](#)
- [Supported datagram formats for sound speed sensors, page 18](#)
- [Supported datagram formats for speed log information, page 19](#)
- [Supported datagram formats for temperature information, page 20](#)
- [Supported datagram formats for wind information, page 20](#)
- [Supported datagram formats for external objects, page 21](#)
- [Supported datagram formats for palette control, page 21](#)
- [Supported datagram formats for motion information, page 22](#)

## Supported datagram formats for annotation data

When you study an echogram, it is often useful to add personal comments to it. Comments can be used to identify specific events such as specific echoes, unusual bottom conditions, or simply for keeping track of time or distance. You can add annotations manually, or import information as datagrams using a serial or LAN (Ethernet) communication port.

The following datagram format is supported:

### ATS Annotation

ATS Annotation is a proprietary datagram format created by Kongsberg Maritime. It allows you to import text annotations from external devices.

### Related topics

- [Supported datagram formats, page 12](#)
- [Inputs, page 13](#)
- [NMEA datagram formats, page 28](#)
- [Proprietary datagram formats, page 46](#)
- [Third-party datagram formats, page 67](#)

## Supported datagram formats for external depth input

The sonar system can receive depth information from an external echo sounder.

The following datagram formats are supported:

### NMEA DBS

The NMEA DBS datagram provides the current depth from the surface. The datagram is no longer recommended for use in new designs. It is frequently replaced by the NMEA DPT datagram format.

### NMEA DBT

The NMEA DBT datagram provides the current depth under the transducer. In new designs, this datagram format is frequently used to replace the DBK and DBS formats.

### NMEA DPT

The NMEA DPT datagram provides the water depth relative to the transducer, and the offset of the measuring transducer.

### Related topics

[Supported datagram formats, page 12](#)

[Inputs, page 13](#)

[NMEA datagram formats, page 28](#)

[Proprietary datagram formats, page 46](#)

[Third-party datagram formats, page 67](#)

## Supported datagram formats for GPS (position) information

Accurate and reliable information from navigation systems are useful for the sonar operation.

When enabled, the vessel's current geographical position is shown on the top bar. The following datagram formats are supported:

59° 27.270<sub>N</sub>  
010° 27.103<sub>E</sub>

### NMEA GLL

The NMEA GLL datagram transfers the latitude and longitude of vessel position, the time of the position fix and the current status from a global positioning system (GPS).

### NMEA GGA

The NMEA GGA datagram transfers time-, position- and fix-related data from a global positioning system (GPS).

### NMEA GGK

The NMEA GGK datagram is used to decode the PTNL, Time, Position, Type and DOP (Dilution of Precision) string of the NMEA 0183 output.

## PTNL,GGK

PTNL ,GGK is a proprietary datagram from Trimble (<https://www.trimble.com>). The PTNL, GGK datagram is longer than the NMEA-0183 standard of 80 characters. The PTNL, GGK datagram is used to decode the time, position, type and dilution of precision of the current position.

## NMEA RMC

The NMEA RMC datagram transfers the time, date, position, course and speed data from a global navigation satellite system (GNSS) receiver.

## NMEA VTG

The NMEA VTG datagram contains the actual course and speed relative to the ground.

## NMEA ZDA

The NMEA ZDA datagram contains the universal time code (UTC), day, month, year and local time zone.

### Related topics

- [Supported datagram formats, page 12](#)
- [Inputs, page 13](#)
- [NMEA datagram formats, page 28](#)
- [Proprietary datagram formats, page 46](#)
- [Third-party datagram formats, page 67](#)

## Supported datagram formats for heading and gyro information

The heading sensor provides the sonar with the vessel's current heading.

When enabled, the vessel's current heading is shown on the top bar. The following datagram formats are supported:



## NMEA HDT

The NMEA HDT datagram provides the true vessel heading. The information is normally provided by a course gyro.

## NMEA HDM

The NMEA HDM datagram provides vessel heading in degrees magnetic. The datagram is no longer recommended for use in new designs. It is often replaced by the NMEA HDG telegram.

## NMEA HDG

The NMEA HDG datagram provides heading from a magnetic sensor. If this reading is corrected for deviation, it produces the magnetic heading. If it is offset by variation, it provides the true heading.

## NMEA THS

The NMEA THS datagram provides the true vessel heading. The datagram includes a mode indicator field providing critical safety-related information about the heading data. The THS datagram replaces the deprecated HDT.

### Related topics

[Supported datagram formats, page 12](#)

[Inputs, page 13](#)

[NMEA datagram formats, page 28](#)

[Proprietary datagram formats, page 46](#)

[Third-party datagram formats, page 67](#)

## Supported datagram formats for trawl information

The data communication from an external trawl system is based on proprietary data formats.

The following datagram formats are supported:

### Simrad DAD

Simrad DAD is a proprietary datagram format created by Kongsberg Maritime to provide the ascending or descending depth rate of the trawl sensor.

### Simrad DBS

Simrad DBS is a proprietary datagram format created by Kongsberg Maritime to provide the current depth of the trawl sensor.

### Simrad GLL

Simrad GLL is a proprietary datagram format created by Kongsberg Maritime to provide the current geographical position of the trawl sensor.

### Simrad HB2

Simrad HB2 is a proprietary datagram format created by Kongsberg Maritime. It provides the vertical distance from the headrope to the footrope (opening), and from the headrope to the bottom (height). It is used for the second trawl in a dual trawl system.

### Simrad HFB

Simrad HFB is a proprietary datagram format created by Kongsberg Maritime. It provides the vertical distance from the headrope to the footrope (opening), and from the headrope to the bottom (height). If you use two height sensors, the information from the second sensor is provided in the Simrad HB2 datagram.

### Simrad MTW

Simrad MTW is a proprietary datagram format created by Kongsberg Maritime to provide the water temperature measured by the trawl sensor.

### **Simrad TDS**

Simrad TDS is a proprietary datagram format created by Kongsberg Maritime to provide the door spread. That is the distance between the two trawl doors. In a dual trawl system, the distance between the second door set is provided in the Simrad TS2 datagram.

### **Simrad TFI**

Simrad TFI is a proprietary datagram format created by Kongsberg Maritime to provide the status information from maximum three catch sensors.

### **Simrad TPC**

Simrad TPC is a proprietary datagram format created by Kongsberg Maritime to provide the trawl position in Cartesian coordinates.

### **Simrad TPR**

Simrad TPR is a proprietary datagram format created by Kongsberg Maritime. It provides the relative bearing and water depth of the trawl sensor, as well as its distance from the vessel. The bearing resolution is 1 degree.

### **Simrad TPT**

Simrad TPT is a proprietary datagram format created by Kongsberg Maritime to provide the true bearing and water depth of the trawl sensor, as well as its distance from the vessel. The bearing resolution is 1 degree.

### **Simrad TS2**

Simrad TS2 is a proprietary datagram format created by Kongsberg Maritime to provide the door spread in a dual trawl system. That is the distance between the two trawl doors. The distance between the first door set is provided in datagram Simrad TDS.

### **Simrad TTS**

Simrad TTS is a proprietary datagram format created by Kongsberg Maritime. It provides the distance between the trawl sensor and the shoal.

### **Related topics**

- [Supported datagram formats, page 12](#)
- [Inputs, page 13](#)
- [NMEA datagram formats, page 28](#)
- [Proprietary datagram formats, page 46](#)
- [Third-party datagram formats, page 67](#)

## Supported datagram formats for catch monitoring information

The data communication from an external catch monitoring system is based on proprietary data formats.

The following datagram formats are supported:

### **Simrad PSIMP,C**

Simrad PSIMP,C a proprietary datagram format created by Kongsberg Maritime to provide sensor configuration data.

### **Simrad PSIMP,D**

Simrad PSIMP,D is a proprietary datagram format created by Kongsberg Maritime to provide the type and configuration of PS and PI sensors used by a Simrad catch monitoring system.

### **Simrad PSIMP,D1**

Simrad PSIMP,D1 is a proprietary datagram format created by Kongsberg Maritime to provide the type and configuration of PS, PI and PX sensors used by a Simrad catch monitoring system.

### **Simrad PSIMP,F**

Simrad PSIMP,F is a proprietary datagram format created by Kongsberg Maritime to provide the type and configuration of PS and PI sensors used by a catch monitoring system.

### **Simrad PSIMP,F1**

Simrad PSIMP,F1 is a proprietary datagram format created by Kongsberg Maritime to provide definition data from catch monitoring sensors.

### **Related topics**

[Supported datagram formats, page 12](#)

[Inputs, page 13](#)

[NMEA datagram formats, page 28](#)

[Proprietary datagram formats, page 46](#)

[Third-party datagram formats, page 67](#)

## Supported datagram formats for sound speed sensors

The **Profile** page in the **Environment** dialog box shows the current sound speed profile. You can select a new profile provided by a CTD (Conductivity, Temperature, Depth) sensor.

The following datagram format is supported:

### **AML Sound speed**

AML is a third-party proprietary datagram format created by AML Oceanographic (<http://www.amloceanographic.com>) for use with their sound velocity probes. The

sound velocity probe output is configurable. The code is searching for a value between 1300 and 1800 and uses it as the sound speed.

### Related topics

- [Supported datagram formats, page 12](#)
- [Inputs, page 13](#)
- [NMEA datagram formats, page 28](#)
- [Proprietary datagram formats, page 46](#)
- [Third-party datagram formats, page 67](#)

## Supported datagram formats for speed log information

An external speed sensor is typically a global positioning system (GPS) or a dedicated speed log.

When enabled, the vessel's current speed is shown on the top bar. The following datagram formats are supported:



### NMEA VTG

The NMEA VTG datagram contains the actual course and speed relative to the ground.

### NMEA VBW

The NMEA VBW datagram contains water- and ground-referenced vessel speed data.

### NMEA VHW

The NMEA VHW datagram contains the compass heading to which the vessel points, and the speed of the vessel relative to the water.

### NMEA CUR

The NMEA CUR datagram contains multi-layer water current data. This includes the depth and speed of the current.

### Related topics

- [Supported datagram formats, page 12](#)
- [Inputs, page 13](#)
- [NMEA datagram formats, page 28](#)
- [Proprietary datagram formats, page 46](#)
- [Third-party datagram formats, page 67](#)

## Supported datagram formats for temperature information

A temperature sensor can be connected to the sonar system.

If a suitable sensor is connected to the sonar system, the top bar may show you the current temperature. The function is offered to allow you to monitor the water temperature, but it will display any temperature reading that is made by the sensor.

The following datagram format is supported:

### NMEA MTW

The NMEA MTW datagram provides the current water temperature.



#### Related topics

[Supported datagram formats, page 12](#)

[Inputs, page 13](#)

[NMEA datagram formats, page 28](#)

[Proprietary datagram formats, page 46](#)

[Third-party datagram formats, page 67](#)

## Supported datagram formats for wind information

A wind sensor can be connected to the sonar system. The sensor provides the direction and speed of the wind

The following datagram formats are supported:

### NMEA MWD

The NMEA MWD datagram provides the direction from which the wind blows across the earth's surface. The wind direction is related to north. The datagram also offers the wind speed.

### NMEA MWV

The NMEA MWV datagram provides the direction from which the wind blows relative to the vessel's centre line.

### NMEA VWR

The NMEA VWR datagram provides the wind angle in relation to the vessel's heading, and the wind speed measured relative to the moving vessel. This datagram format is not recommended for use in new designs. It has been replaced by the MWV datagram format.

#### Related topics

[Supported datagram formats, page 12](#)

[Inputs, page 13](#)

[NMEA datagram formats, page 28](#)

[Proprietary datagram formats, page 46](#)

[Third-party datagram formats, page 67](#)

## Supported datagram formats for external objects

The following datagram formats are supported:

### NMEA TLL

The NMEA TLL datagram contains target information; number, name, position and time tag. The TLL datagram allows the sonar system to receive information about targets that are tracked by other systems.

### Serpe BSC

Serpe BSC is a proprietary datagram format created by Serpe. It is supplied with buoys and provides the geographical location of the buoy as well as the water temperature the buoy measures.

### Ryokusei RBY

Ryokusei RBY is a proprietary datagram format created by Ryokusei. It is supplied with buoys and provides the geographical location of the buoy as well as the water temperature the buoy measures. The datagram also provides echo sounder information.

#### Related topics

[Supported datagram formats, page 12](#)

[Inputs, page 13](#)

[NMEA datagram formats, page 28](#)

[Proprietary datagram formats, page 46](#)

[Third-party datagram formats, page 67](#)

## Supported datagram formats for palette control

On some vessels, the sonar is used as an integrated part of a large information system. In such cases, the host system may offer a common palette control. This allows you to select a common colour scheme ("skin") used in all the presentations.

The following datagram format is supported:

### NMEA DDC

The NMEA DDC (Display Dimming and Control) datagram format allows you to remotely control the colour palette and brightness of the sonar display presentations.

#### Related topics

[Supported datagram formats, page 12](#)

[Inputs, page 13](#)

[NMEA datagram formats, page 28](#)

[Proprietary datagram formats, page 46](#)

[Third-party datagram formats, page 67](#)

## Supported datagram formats for motion information

The sonar system interfaces peripheral systems and sensors using standard and/or proprietary datagram formats.

The sonar system supports the following datagram formats from a motion sensor:

When enabled, the navigational information on the top bar includes the vessel's current roll, pitch and heave movements. The following datagram formats are supported:



### KM Binary

KM Binary is a generic datagram format defined by Kongsberg Maritime. This format has very high resolution on timing and sensor parameters.

### Kongsberg EM Attitude 3000

The Kongsberg EM Attitude 3000 is a proprietary datagram format created by Kongsberg Maritime for use with digital motion sensors. It holds roll, pitch, heave and heading information.

### Furuno GPatt

Furuno GPatt is a proprietary datagram format created by Furuno (<http://www.furuno.jp>) to contain pitch, roll and yaw information.

### Furuno GPhve

Furuno GPhve is a proprietary datagram format created by Furuno (<http://www.furuno.jp>) to contain heave information.

### Hemisphere GNSS GPHEV

GPHEV is a proprietary datagram format created by Hemisphere GNSS (<https://hemispherengnss.com>) to contain heave information.

### Teledyne TSS1

Teledyne TSS1 is a proprietary datagram format created by Teledyne TSS Navigation Systems for heave, roll and pitch compensation. When you select this protocol, the number of sensor variables is fixed, and there is no token associated with it.

### Related topics

- [Supported datagram formats, page 12](#)
- [Inputs, page 13](#)
- [NMEA datagram formats, page 28](#)
- [Proprietary datagram formats, page 46](#)
- [Third-party datagram formats, page 67](#)

# Outputs

## Topics

[Supported datagram formats for target marker outputs, page 23](#)

### Supported datagram formats for target marker outputs

Use the **Output Marker** page to export target markers to a communication port. Each marker is identified with its geographical location. This marker location can be very useful for other instruments. For example, you can export this information to a chartplotter.

The following datagram formats are supported:

#### MDS

Simrad MDS is a proprietary datagram format created by Kongsberg Maritime. It contains the location, bearing and depth of a tracked target. All information is presented relative to your own vessel. All data are related to the tracked target.

#### TPP

Simrad TPP is a proprietary datagram format created by Kongsberg Maritime. It exports the horizontal range, bearing and depth of a tracked target. All data are related to the tracked target.

#### NMEA TLL

The NMEA TLL datagram contains target information; number, name, position and time tag. The TLL datagram allows the sonar system to export information about the currently tracked targets.

#### Related topics

[Supported datagram formats, page 12](#)

[Outputs, page 23](#)

[NMEA datagram formats, page 28](#)

[Proprietary datagram formats, page 46](#)

[Third-party datagram formats, page 67](#)

# Datagram formats

## Topics

[About NMEA and standard datagram formats, page 25](#)

[NMEA datagram formats, page 28](#)

[Proprietary datagram formats, page 46](#)

[Third-party datagram formats, page 67](#)

# About NMEA and standard datagram formats

## Topics

- [About the NMEA datagram formats, page 25](#)
- [NMEA, page 26](#)
- [NMEA sentence structure, page 26](#)
- [Standard NMEA 0183 communication parameters, page 27](#)

## About the NMEA datagram formats

The sonar system can send and receive information to and from several different peripherals. All transmissions take place as *datagrams* with data sentences. Each datagram has a defined format and length.

The NMEA 0183 standard is the most common protocol used to receive and transmit data to and from peripheral sensors. A parametric sentence structure is used for all NMEA data.

The sentence starts with a “\$” delimiter and represents the majority of approved sentences defined by the standard. This sentence structure with delimited and defined data files, is the preferred method for conveying information.

For more information about the NMEA standard, the format and the data sentences, refer to NMEA’s official publications. The *NMEA 1083 - Standard for Interfacing Marine Electronic Devices* document explains the formats in detail. The document can be obtained from NMEA.

### Note

---

*The terms "Datagram" and "telegram" are generally used to describe the basic transfer unit associated with a packet-switched network. The term "sentence" is also used. In this publication, we use the term "datagram".*

---

## Related topics

- [Supported datagram formats, page 12](#)
- [About NMEA and standard datagram formats, page 25](#)
- [Datagram formats, page 24](#)

## NMEA

The National Marine Electronics Association (NMEA) has defined communication standards for maritime electronic equipment. The sonar system supports these standards for communication with external sensors and peripheral devices.

The most common standard is NMEA 0183. The National Marine Electronics Association describes it as follows:

The NMEA 0183 Interface Standard defines electrical signal requirements, data transmission protocol and time, and specific sentence formats for a 4800-baud serial data bus. Each bus can have only one talker but many listeners.

*National Marine Electronics Association*

For more information about the National Marine Electronics Association and the NMEA 0183 standard, refer to the organization's web site at:

- <http://www.nmea.org>

### Related topics

[Supported datagram formats, page 12](#)

[About NMEA and standard datagram formats, page 25](#)

[Datagram formats, page 24](#)

## NMEA sentence structure

A sentence structure is defined by NMEA to establish the communication between two units. Most other datagram formats are designed using the same, or a similar, structure.

The following provides a summary explanation of the approved parametric sentence structure:

\$aaccc,c-c\*hh<CR><LF>

\$

This character (Hex: 24) is used to identify the start of a sentence.

**aaccc**

This is the address field. The first two characters (aa) identify the *talker ID*, while the last three characters are the *sentence formatter* mnemonic code identifying the data type and the string format of the successive fields.

,

The comma (Hex: 2C) is used as a *field delimiter*. This character starts each field except the address and checksum fields. If it is followed by a null field, it is all that remains to indicate that there are no data in the field.

**c-c**

This is the *data sentence block*. This is a series of data fields containing all the data to be transmitted. The data field sentence is fixed and identified by the sentence

formatter in the address field. Data fields may be of variable length, and they are preceded by the field delimiter.

\*

This character (Hex: 2A) is the *checksum delimiter*. This delimiter follows the last field of the sentence and indicates that the following two alphanumerical characters contain the checksum.

## hh

This is the *checksum*.

## <CR><LF>

The carriage return and line feed characters terminate the datagram sentence.

### Note

---

*In some proprietary datagrams received from other Kongsberg Maritime equipment, the \$ character is replaced by the @ character. The checksum field may then not be in use.*

---

## Related topics

[Supported datagram formats, page 12](#)

[About NMEA and standard datagram formats, page 25](#)

[Datagram formats, page 24](#)

## Standard NMEA 0183 communication parameters

The sonar system uses both NMEA and proprietary datagram formats to communicate with peripheral systems and sensors. The majority of the datagrams used by the sonar system are defined by the National Marine Electronics Association (NMEA). NMEA has defined a fixed set of transmission parameters.

The communication parameters defined for NMEA 0183 are:

- **Baud rate:** 4800 bit/s
- **Data bits:** 8
- **Parity:** Even
- **Stop bits:** 1

Some instruments may provide other parameters and/or options. You must always check the relevant technical documentation supplied by the manufacturer.

## Related topics

[Supported datagram formats, page 12](#)

[About NMEA and standard datagram formats, page 25](#)

[Datagram formats, page 24](#)

# NMEA datagram formats

## Topics

- [NMEA CUR datagram format, page 28](#)
- [NMEA DBS datagram format, page 30](#)
- [NMEA DBT datagram format, page 30](#)
- [NMEA DDC datagram format, page 31](#)
- [NMEA DPT datagram format, page 32](#)
- [NMEA GGA datagram format, page 33](#)
- [NMEA GGK datagram format, page 34](#)
- [NMEA GLL datagram format, page 35](#)
- [NMEA HDG datagram format, page 35](#)
- [NMEA HDM datagram format, page 36](#)
- [NMEA HDT datagram format, page 37](#)
- [NMEA MTW datagram format, page 37](#)
- [NMEA MWD datagram format, page 38](#)
- [NMEA MWV datagram format, page 38](#)
- [NMEA RMC datagram format, page 39](#)
- [NMEA THS datagram format, page 40](#)
- [NMEA TLL datagram format, page 40](#)
- [NMEA VBW datagram format, page 41](#)
- [NMEA VHW datagram format, page 42](#)
- [NMEA VTG datagram format, page 43](#)
- [NMEA VWR datagram format, page 44](#)
- [NMEA ZDA datagram format, page 44](#)

## NMEA CUR datagram format

The NMEA CUR datagram contains multi-layer water current data. This includes the depth and speed of the current.

### Format

```
$--CUR,A,x,d,l.l,m.m,x.x,a,k.k,r.r,h.h,a,a,*hh<CR><LF>
```

## Description

This description is not complete. For additional details, refer to the NMEA standard.

- 1    \$—: Talker identifier
- 2    **CUR**: Datagram identifier
- 3    **A**: Validity
  - **A** = The data are valid.
  - **V** = The data are not valid.
- 4    **d**: Data set number (1 - 9)
- 5    **l.l**: Layer number
- 6    **m.m**: Depth (Metres)
- 7    **x.x**: Sea current direction in degrees
- 8    **a**: Direction reference in use
  - **T** = True
  - **R** = Relative
- 9    **k.k**: Sea current speed in knots
- 10    **r.r**: Reference layer depth in metres
- 11    **h.h**: Heading
- 12    **a**: Heading reference
  - **T** = True
  - **M** = Magnetic
- 13    **a**: Speed reference
  - **B** = Bottom track
  - **W** = Water track
  - **P** = Positioning system
- 14    \***hh**: Checksum

## Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[NMEA datagram formats, page 28](#)

## NMEA DBS datagram format

The NMEA DBS datagram provides the current depth from the surface. The datagram is no longer recommended for use in new designs. It is frequently replaced by the NMEA DPT datagram format.

### Format

```
$--DBS,x.x,f,y.y,M,z.z,F*hh<CR><LF>
```

### Description

All depths are measured from below the sea surface.

- 1    \$—: Talker identifier
- 2    **DBS**: Datagram identifier
- 3    **x.x,f**: Depth (Feet)
- 4    **y.y,M**: Depth (Metres)
- 5    **z.z,F**: Depth (Fathoms)
- 6    \***hh**: Checksum

Tip

---

*If you need the depth below the keel, use the NMEA DBK datagram. If you need the depth below the transducer, use the NMEA DBT datagram.*

---

### Related topics

- [Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[NMEA datagram formats, page 28](#)

## NMEA DBT datagram format

The NMEA DBT datagram provides the current depth under the transducer. In new designs, this datagram format is frequently used to replace the DBK and DBS formats.

### Format

```
$--DBT,x.x,f,y.y,M,z.z,F*hh<CR><LF>
```

### Description

All depths are measured from below the transducer face.

- 1    \$—: Talker identifier
- 2    **DBT**: Datagram identifier

- 3 **x.x,f:** Depth (Feet)
- 4 **y.y,M:** Depth (Metres)
- 5 **z.z,F:** Depth (Fathoms)
- 6 **\*hh:** Checksum

**Tip**


---

*If you need the depth below the keel, use the NMEA DBK datagram. If you need the depth below the surface, use the NMEA DBS datagram.*

---

**Related topics**

- [Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[NMEA datagram formats, page 28](#)

**NMEA DDC datagram format**

The NMEA DDC (Display Dimming and Control) datagram format allows you to remotely control the colour palette and brightness of the sonar display presentations.

**Format**

```
$--DDC,a,xx,b,c*hh<CR><LF>
```

**Description**

- 1 **\$—:** Talker identifier
- 2 **DDC:** Datagram identifier
- 3 **a:** Display dimming
  - **D** = Daytime setting
  - **K** = Dusk setting
  - **N** = Nighttime setting
  - **O** = The display backlight is turned off.
- 4 **xx:** Brightness (Percentage)
- 5 **a:** Colour palette
  - **D** = Daytime setting
  - **K** = Dusk setting
  - **N** = Nighttime setting
  - **O** = The display backlight is turned off.
- 6 **a:** Status

- **R** = The datagram is provided as a status report.
- **C** = The datagram is provided as a command to change settings.

This datagram description is not complete. For more information, refer to the source specifications issued by National Marine Electronics Association (NMEA).

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[NMEA datagram formats, page 28](#)

## NMEA DPT datagram format

The NMEA DPT datagram provides the water depth relative to the transducer, and the offset of the measuring transducer.

### Format

```
$--DPT,x.x,y.y,z.z*hh<CR><LF>
```

### Description

This description is not complete. For additional details, refer to the NMEA standard.

- 1 **\$—:** Talker identifier
- 2 **DPT:** Datagram identifier
- 3 **x.x:** Depth (Metres) Relative to the transducer
- 4 **y.y:** Offset (Metres) Relative to the transducer
  - Positive offset numbers provide the distance from the transducer to the water line.
  - Negative offset numbers provide the distance from the transducer to the part of the keel of interest.
- 5 **z.z:** This is the maximum range scale in use.
- 6 **\*hh:** Checksum

### Tip

---

*If you need the depth below the keel, use the NMEA DBK datagram. If you need the depth below the surface, use the NMEA DBS datagram. If you need the depth below the transducer, use the NMEA DBT datagram.*

---

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[NMEA datagram formats, page 28](#)

## NMEA GGA datagram format

The NMEA GGA datagram transfers time-, position- and fix-related data from a global positioning system (GPS).

### Format

```
$--GGA, hhmmss.ss, llll.ll,a, yyyy.y, yy, a,x, zz, d.d, a.a,M, g.g,M, r.r, cccc*hh
```

### Description

- 1    **\$—:** Talker identifier
- 2    **GGA:** Datagram identifier
- 3    **hhmmss.ss:** Coordinated Universal Time (UTC) of the current position
- 4    **llll.ll,a:** Latitude, North/South (Degrees, minutes and hundredths)
  - **N** = North
  - **S** = South
- 5    **yyyy.yy,a:** Longitude, East/West (Degrees, minutes and hundredths)
  - **E** = East
  - **W** = West
- 6    **x:** Quality indicator for the GPS (Global Positioning System) (Refer to the NMEA standard for further information about the GPS quality indicator.)
- 7    **zz:** Number of satellites in use: (00 - 12) (The number of satellites may be different from the number in view.)
- 8    **d.d:** HDOP (Horizontal dilution of precision)
- 9    **a.a,M:** Altitude related to mean sea level (geoid) (Metres)
- 10    **g.g,M:** Geoidal separation (Metres)
- 11    **r.r:** Age of GPS (Global Positioning System) data
- 12    **cccc:** Identification of differential reference station: (0000 - 1023)
- 13    **\*hh:** Checksum

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[NMEA datagram formats, page 28](#)

## NMEA GGK datagram format

The NMEA GGK datagram is used to decode the PTNL, Time, Position, Type and DOP (Dilution of Precision) string of the NMEA 0183 output.

### Format

```
$--GGK, hhmmss.ss, ddmmyy, nnnnn.nnnnnnnn, a, yyyy.yyyyyyyy, a, x, zz, w.w, EHTeeeeee, u*hh<CR><LF>
```

### Description

- 1   **\$—**: Talker identifier
- 2   **GGK**: Datagram identifier
- 3   **hhmmss.ss**: Coordinated Universal Time (UTC) of the current position
- 4   **ddmmyy**: Day, month and year
- 5   **nnnn.nnnnnnnn,a**: Latitude, North/South (Degrees, minutes and hundredths)
  - **N** = North
  - **S** = South
- 6   **yyyy.yyyyyyyy,a**: Longitude, East/West (Degrees, minutes and hundredths)
  - **E** = East
  - **W** = West
- 7   **x**: Quality indicator for the GPS (Global Positioning System) (Refer to the NMEA standard for further information about the GPS quality indicator.)
- 8   **zz**: Number of satellites in use (00 - 12) (The number of satellites may be different from the number in view.)
- 9   **w.w**: PDOP (Position dilution of precision)
- 10   **EHTeeeeee**: Ellipsoidal height of fix
- 11   **u**: Unit of height measurement
- 12   **\*hh**: Checksum

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[NMEA datagram formats, page 28](#)

## NMEA GLL datagram format

The NMEA GLL datagram transfers the latitude and longitude of vessel position, the time of the position fix and the current status from a global positioning system (GPS).

### Format

```
$--GLL,1111.11,a,yyyyy.yy,a,hhmmss.ss,A,a*hh<CR><LF>
```

### Description

- 1   **\$**—: Talker identifier
- 2   **GLL**: Datagram identifier
- 3   **lll.ll,a**: Latitude, North/South (Degrees, minutes and hundredths)
  - **N** = North
  - **S** = South
- 4   **yyyy.y,yy,a**: Longitude, East/West (Degrees, minutes and hundredths)
  - **E** = East
  - **W** = West
- 5   **hhmmss.ss**: Coordinated Universal Time (UTC) of the current position
- 6   **A**: Status
  - **A** = The data are valid.
  - **V** = The data are not valid.
- 7   **a**: Mode indicator
- 8   **\*hh**: Checksum

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[NMEA datagram formats, page 28](#)

## NMEA HDG datagram format

The NMEA HDG datagram provides heading from a magnetic sensor. If this reading is corrected for deviation, it produces the magnetic heading. If it is offset by variation, it provides the true heading.

### Format

```
$--HDG,x.x,z.z,a,r.r,a*hh<CR><LF>
```

## Description

- 1    \$—: Talker identifier
- 2    **HDG**: Datagram identifier
- 3    x.x: (Degrees (Magnetic))
- 4    z.z,a: Deviation (Degrees (Magnetic)), East/West
  - W = West
  - E = East
- 5    r.r,a Variation (Degrees (Magnetic)), East/West
  - W = West
  - E = East
- 6    \*hh: Checksum

## Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[NMEA datagram formats, page 28](#)

## NMEA HDM datagram format

The NMEA HDM datagram provides vessel heading in degrees magnetic. The datagram is no longer recommended for use in new designs. It is often replaced by the NMEA HDG telegram.

## Format

```
$--HDM,x.x,M*hh<CR><LF>
```

## Description

- 1    \$—: Talker identifier
- 2    **HDM**: Datagram identifier
- 3    x.x,M: (Degrees, Magnetic)
- 4    \*hh: Checksum

## Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[NMEA datagram formats, page 28](#)

## NMEA HDT datagram format

The NMEA HDT datagram provides the true vessel heading. The information is normally provided by a course gyro.

### Format

```
$--HDT,x.x,T*hh<CR><LF>
```

### Description

- 1    \$—: Talker identifier
- 2    **HDT**: Datagram identifier
- 3    x.x,T: Heading (Degrees, True)
- 4    \*hh: Checksum

### Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[NMEA datagram formats, page 28](#)

## NMEA MTW datagram format

The NMEA MTW datagram provides the current water temperature.

### Format

```
$--MTW,x.x,C*hh<CR><LF>
```

### Description

- 1    \$—: Talker identifier
- 2    **MTW**: Datagram identifier
- 3    x.x,C: Temperature (Degrees, Celsius)
- 4    \*hh: Checksum

### Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[NMEA datagram formats, page 28](#)

## NMEA MWD datagram format

The NMEA MWD datagram provides the direction from which the wind blows across the earth's surface. The wind direction is related to north. The datagram also offers the wind speed.

### Format

```
$--MWD,x.x,T,y.y,M,z.z,N,s.s,M*hh<CR><LF>
```

### Description

- 1    \$—: Talker identifier
- 2    **MWD**: Datagram identifier
- 3    **x.x,T**: Wind direction (True) (0 to 359 degrees)
- 4    **y.y,M**: Wind direction (Magnetic) (0 to 359 degrees)
- 5    **z.z,N**: Wind speed (knots)
- 6    **s.s,M**: Wind speed (metres/second)
- 7    \***hh**: Checksum

### Related topics

- [Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[NMEA datagram formats, page 28](#)

## NMEA MWV datagram format

The NMEA MWV datagram provides the direction from which the wind blows relative to the vessel's centre line.

### Format

```
$--MWV,x.x,a,y.y,b*hh<CR><LF>
```

### Description

- 1    \$—: Talker identifier
- 2    **MWV**: Datagram identifier
- 3    **x.x**: NMEA MWV (0 to 359 degrees)
- 4    **a**: Reference
  - **R** = Relative
  - **T** = Theoretical

- 5   **y.y:** Wind speed
- 6   **b:** Wind speed unit (K/M/N/S)
- 7   **\*hh:** Checksum

### Related topics

- [Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[NMEA datagram formats, page 28](#)

## NMEA RMC datagram format

The NMEA RMC datagram transfers the time, date, position, course and speed data from a global navigation satellite system (GNSS) receiver.

### Format

```
$--RMC,hhmmss.ss,A,ffff.ll,a,yyyyyy.yy,a,x.x,z.z,ddmmyy,r.r,a,a*hh
```

### Description

- 1   **\$—:** Talker identifier
- 2   **RMC:** Datagram identifier
- 3   **hhmmss.ss:** Coordinated Universal Time (UTC) of the current position
- 4   **A:** Status
  - **A** = The data are valid.
  - **V** = The data are not valid.
- 5   **ffff.ll,a:** Latitude, North/South (Degrees, minutes and hundredths)
  - **N** = North
  - **S** = South
- 6   **yyyyyy.yy,a:** Longitude, East/West (degrees, minutes and hundredths)
  - **W** = West
  - **E** = East
- 7   **x.x:** Speed over ground (knots)
- 8   **z.z:** Course over ground (degrees (True))
- 9   **ddmmyy:** Date
- 10   **r.r,a:** Magnetic variation, East/West (degrees)
  - **E** = East
  - **W** = West

11 **a**: Mode indicator

12 **\*hh**: Checksum

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[NMEA datagram formats, page 28](#)

## NMEA THS datagram format

The NMEA THS datagram provides the true vessel heading. The datagram includes a mode indicator field providing critical safety-related information about the heading data. The THS datagram replaces the deprecated HDT.

### Format

```
$--HETHS,x.xx,a*hh<CR><LF>
```

### Description

1 **\$—**: Talker identifier

2 **HETHS**: Datagram identifier

3 **x.xx**: Heading (Degrees)

4 **a**: Mode

- **A**: Autonomous
- **V**: The data are not valid.

5 **\*hh**: Checksum

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[NMEA datagram formats, page 28](#)

## NMEA TLL datagram format

The NMEA TLL datagram contains target information; number, name, position and time tag. The TLL datagram allows the sonar system to receive information about targets that are tracked by other systems.

### Format

```
$--TLL,xx,1111.11,a,yyyy.y,aa,c--c,hmmss.ss,ab*hh <CR><LF>
```

## Description

- 1    \$—: Talker identifier
- 2    **TLL**: Datagram identifier
- 3    xx: Target number
- 4    lll.ll,a: Target latitude
  - **N** = North
  - **S** = South
- 5    yyyy.yy,a: Target longitude
  - **E** = East
  - **W** = West
- 6    c--c: Target name
- 7    hhmmss.ss: Coordinated Universal Time (UTC)
- 8    a: Target status
  - **L** = Lost
  - **Q** = Query
  - **T** = Tracking
- 9    b: Value is set to "R" if target is a reference used to determined own-ship position or velocity.
- 10   \*hh: Checksum

## Related topics

- [Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[NMEA datagram formats, page 28](#)

## NMEA VBW datagram format

The NMEA VBW datagram contains water- and ground-referenced vessel speed data.

### Format

```
$--VBW,x.x,z.z,A,r.r,q.q,A,p.p,A,c.c,A*hh<CR><LF>
```

## Description

- 1    \$—: Talker identifier
- 2    **VBW**: Datagram identifier
- 3    x.x: Speed relative to water, Longitudinal (knots)

- 4 **z.z**: Speed relative to water, Transverse (knots)
- 5 **A**: Speed relative to water, Status
  - **A** = The data are valid.
  - **V** = The data are not valid.
- 6 **r.r**: Speed relative to ground, Longitudinal (knots)
- 7 **q.q**: Speed relative to ground, Transverse (knots)
- 8 **A**: Speed relative to ground, Status
  - **A** = The data are valid.
  - **V** = The data are not valid.
- 9 **p.p**: Speed relative to water, Stern, Transverse (knots)
- 10 **A**: Speed relative to water, Stern, Status
  - **A** = The data are valid.
  - **V** = The data are not valid.
- 11 **c.c**: Speed relative to ground, Stern, Transverse (knots)
- 12 **A**: Speed relative to ground, Stern, Status
  - **A** = The data are valid.
  - **V** = The data are not valid.
- 13 **\*hh**: Checksum

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[NMEA datagram formats, page 28](#)

## NMEA VHW datagram format

The NMEA VHW datagram contains the compass heading to which the vessel points, and the speed of the vessel relative to the water.

### Format

```
$--VHW,x.x,T,x.x,M,x.x,N,x.x,K*hh<CR><LF>
```

### Description

- 1 **\$—**: Talker identifier
- 2 **VHW**: Datagram identifier
- 3 **x.x,T**: Heading (Nautical miles)

- 
- 4 **x.x,M:** Heading (Degrees (Magnetic))
  - 5 **x.x,N:** Speed relative to water (knots), Resolution = 0.1 knots
  - 6 **x.x,K:** Speed relative to water (km/h), Resolution = 0.1 km/h
  - 7 **\*hh:** Checksum

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[NMEA datagram formats, page 28](#)

## NMEA VTG datagram format

The NMEA VTG datagram contains the actual course and speed relative to the ground.

### Format

```
$--VTG,x.x,T,y.y,M,z.z,N,g.g,K,a*hh<CR><LF>
```

### Description

- 1 **\$—:** Talker identifier
- 2 **VTG:** Datagram identifier
- 3 **x.x,T:** Course over ground (Degrees, True)
- 4 **y.y,M:** Course over ground (Degrees, Magnetic)
- 5 **z.z,N:** Speed over ground (knots)
- 6 **g.g,K:** Speed over ground (km/h)
- 7 **a:** Mode indicator
  - A = Autonomous
  - D = Differential
  - N = The data are not valid.
- 8 **\*hh:** Checksum

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[NMEA datagram formats, page 28](#)

## NMEA VWR datagram format

The NMEA VWR datagram provides the wind angle in relation to the vessel's heading, and the wind speed measured relative to the moving vessel.

### Note

---

*This datagram format is not recommended for use in new designs. It has been replaced by the MWV datagram format.*

---

### Format

```
$--VWR,x.x,a,y.y,N,z.z,M,s.s,K*hh<CR><LF>
```

### Description

- 1    \$—: Talker identifier
- 2    **VWR**: Datagram identifier
- 3    **x.x**: Wind angle (0 to 180 degrees)
- 4    **a**: Reference
  - **L** = Left
  - **R** = Right
- 5    **y.y,N**: Wind speed (knots)
- 6    **z.z,M**: Wind speed (metres/second)
- 7    **s.s,K**: Wind speed (kilometres/hour)
- 8    **\*hh**: Checksum

### Related topics

- [Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[NMEA datagram formats, page 28](#)

## NMEA ZDA datagram format

The NMEA ZDA datagram contains the universal time code (UTC), day, month, year and local time zone.

### Format

```
$--ZDA,hhmmss.ss,xx,yy,zzzz, hh, mm*hh<CR><LF>
```

## Description

This description is not complete. For additional details, refer to the NMEA standard.

- 1   **\$—:** Talker identifier
- 2   **ZDA:** Datagram identifier
- 3   **hhmmss.ss:** Coordinated Universal Time (UTC) of the current position
- 4   **xx:** Day (01 - 31) (Part of UTC)
- 5   **yy:** Month (01 - 12) (Part of UTC)
- 6   **zzzz:** Year (Part of UTC)
- 7   **hh:** Local time zone, (00 - ±13)
- 8   **mm:** Local time zone, (00 - 59)
- 9   **\*hh:** Checksum

## Related topics

- [Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[NMEA datagram formats, page 28](#)

# Proprietary datagram formats

## Topics

- [ATS Annotation datagram format, page 46](#)
- [Simrad PSIMP,C datagram format, page 47](#)
- [Simrad PSIMP,D datagram format, page 49](#)
- [Simrad PSIMP,F datagram format, page 51](#)
- [Simrad DAD datagram format, page 52](#)
- [Simrad DBS datagram format, page 52](#)
- [Simrad GLL datagram format, page 53](#)
- [Simrad HB2 datagram format, page 53](#)
- [Simrad HFB datagram format, page 54](#)
- [Simrad MTW datagram format, page 55](#)
- [Simrad TDS datagram format, page 55](#)
- [Simrad TFI datagram format, page 56](#)
- [Simrad TPC datagram format, page 56](#)
- [Simrad TPR datagram format, page 57](#)
- [Simrad TPT datagram format, page 58](#)
- [Simrad TS2 datagram format, page 59](#)
- [Simrad TTS datagram format, page 59](#)
- [Simrad MDS datagram format, page 60](#)
- [Simrad TPP datagram format, page 61](#)
- [Kongsberg EM Attitude 3000 datagram format, page 62](#)
- [KM Binary datagram format, page 64](#)

## ATS Annotation datagram format

ATS Annotation is a proprietary datagram format created by Kongsberg Maritime. It allows you to import text annotations from external devices.

### Format

```
$??ATS,tttt<CR><LF>
```

## Description

- 1 ???: talker identifier
- 2 **ATS**: datagram identifier
- 3 **ttt**: free text

## Related topics

- [Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Proprietary datagram formats, page 46](#)

## Simrad PSIMP,C datagram format

Simrad PSIMP,C a proprietary datagram format created by Kongsberg Maritime to provide sensor configuration data.

### Format

```
$PSIMP,C,tt,dd,M,U,DT,VS,FF,SWuC,SWDSP,cal,find,agc,mgain,mpf,mpfl,if,ifl*chksum<CR><LF>
```

## Description

### Note

*This datagram description is not complete. For more information, contact Kongsberg Maritime.*

- 
- 1 **PS**: Talker identifier
  - 2 **IMP**: Datagram identifier
  - 3 **C**: Sentence specifier
  - 4 **tt**: Time
  - 5 **dd**: Date
  - 6 **M**: Unit of measurement; Depth
    - **M** = metres
    - **f** = feet
    - **F** = fathoms
    - **P** = Passi braccio
  - 7 **U**: Unit of measurement; Temperature
    - **C** = Celsius
    - **F** = Fahrenheit
  - 8 **TD**: Detection threshold, Receiver, 3 to 20 dB

- 9 **VS:** Vessel speed, 1 to 20 knots (This is the maximum speed of the vessel during the pursuing operations.)
- 10 **FF:** This is a 2-character field with filter settings for the digital, analogue and hybrid sensors. The left character identifies the filter setting for the digital sensors. The right character identifies filter setting for the analogue and hybrid sensors.
- **0** = Off
  - **1** = Weak
  - **2** = Medium
  - **3** = Strong
- 11 **SWuC:** Software version, Microcontroller
- 12 **SWDSP:** Software version, Digital Signal Processor (DSP)
- 13 **cal:** Value ="1" to initiate depth sensor calibration
- 14 **find:** Value ="1" to initiate sensor finder (not implemented)
- 15 **agc:** AGC (Automatic Gain Control)
- **0** = Off
  - **1** = Active
- 16 **mgain:** Manual gain (AGC (Automatic Gain Control) = Off)
- 0 dB
  - 20 dB
  - 40 dB
- 17 **mpf:** Multipath filter
- **0** = Off
  - **1** = Active
- 18 **mpfl:** Multipath filter (Value)
- **0** = Test
  - **1** = Fresh
  - **2** = Salt
- 19 **if:** Interference filter
- **0** = Off
  - **1** = Active
- 20 **ifl:** Interference filter level = 0 - 9
- 21 **chksum:** Checksum (The checksum field consists of a "\*" and two hex digits representing the exclusive OR of all characters between, but not including, the "\$" and "\*" characters.)

**Note** \_\_\_\_\_

*This datagram format is obsolete. It is no longer in use on new designs.*

---

**Related topics**

- [Supported datagram formats, page 12](#)
- [Datagram formats, page 24](#)
- [Proprietary datagram formats, page 46](#)

## Simrad PSIMP,D datagram format

Simrad PSIMP ,D is a proprietary datagram format created by Kongsberg Maritime to provide the type and configuration of PS and PI sensors used by a Simrad catch monitoring system.

### Format

```
$PSIMP,D,tt,dd,M,U,S,C,V,Cr,Q,In,SL,NL,G,Cb,error*chksum<CR><LF>
```

### Description

**Note** \_\_\_\_\_

*This datagram description is not complete. For more information, contact Kongsberg Maritime.*

---

- 1 **PS:** Talker identifier
- 2 **IMP:** Datagram identifier
- 3 **D:** Sentence specifier
- 4 **tt:** Time
- 5 **dd:** Date
- 6 **M:** Type of measurement
  - **D** = Depth
  - **T** = Temperature
  - **C** = Catch
  - **B** = Bottom
  - **N** = No sensor
  - **M** = Marker
- 7 **U:** Unit of measurement
  - **M** = Depth measurements (metres)

- **f** = Depth measurements (feet)
  - **F** = Depth measurements (fathoms)
  - **C** = Temperature measurements (Celsius)
  - **F** = Temperature measurements (Fahrenheit)
- 8   **S:** Sensor number (1, 2, 3)
- 9   **C:** Channel (This is the number of the communication channel for the current data source. (1 - 30))
- 10   **V:** Value (This is the magnitude of the measurement made by the sensor.)
- 11   **Cr:** Change rate
- 12   **Q:** Quality
  - **0** = There is no connection between the sensor and the receiver.
  - **1** = One or two telemetry pulses are lost. The measured value is predicted.
  - **2** = The measured data is reliable.
- 13   **In:** Interference
  - **0** = Interference is not detected.
  - **1** = Interference is detected.
- 14   **SL:** Signal level (dB // 1 µPa)
- 15   **NL:** Noise level (dB // 1 µPa)
- 16   **G:** Gain (0, 20 or 40 dB)
- 17   **Cb:** Cable quality
  - **0** = The cable is not connected.
  - **1** = The cable is in good working order.
  - **2** = The cable is short-circuited, or the hydrophone current is too large.
- 18   **error:** Error (**0** means that no errors are detected. Any other value indicates an error condition.)
- 19   **chksum:** Checksum (The checksum field consists of a "\*" and two hex digits representing the exclusive OR of all characters between, but not including, the "\$" and "\*" characters.)

**Note** \_\_\_\_\_

*This datagram format is obsolete. It is no longer in use on new designs. It has been replaced by datagram PSIMP ,D1.*

---

**Related topics**

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[Proprietary datagram formats, page 46](#)

## Simrad PSIMP,F datagram format

Simrad PSIMP,F is a proprietary datagram format created by Kongsberg Maritime to provide the type and configuration of PS and PI sensors used by a catch monitoring system.

### Format

```
$PSIMP,F,S1,S2,S3,T1,T2,T3,F1,F2,F3*checksum<CR><LF>
```

### Description

#### Note

*This datagram description is not complete. For more information, contact Kongsberg Maritime.*

- 1 **PS:**Talker identifier
- 2 **IMP:** Datagram identifier
- 3 **F:** Sentence specifier
- 4 **S1,S2,S3:** Sensor types
  - **D** = Depth (300 metres)
  - **E** = Depth (600 metres)
  - **T** = Temperature
  - **C** = Catch (Slow)
  - **F** = Catch (Fast)
  - **B** = Bottom
  - **N** = No sensor
- 5 **T1,T2,T3:** Channel
- 6 **F1,F2,F3:** Offset
- 7 **checksum:** Checksum (The checksum field consists of a "\*" and two hex digits representing the exclusive OR of all characters between, but not including, the "\$" and "\*" characters.)

### Related topics

- [Supported datagram formats, page 12](#)
- [Datagram formats, page 24](#)
- [Proprietary datagram formats, page 46](#)

## Simrad DAD datagram format

Simrad DAD is a proprietary datagram format created by Kongsberg Maritime to provide the ascending or descending depth rate of the trawl sensor.

### Format

```
@IIDAD,x.x,M,y.y,M<CR><LF>
```

### Description

- 1 **II**: Talker identifier
- 2 **DAD**: Datagram identifier
- 3 **x.x,M**: Depth (Metres)
- 4 **y.y,M**: Depth changes (Metres/Minutes) The value is negative when the depth is ascending.

### Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Proprietary datagram formats, page 46](#)

## Simrad DBS datagram format

Simrad DBS is a proprietary datagram format created by Kongsberg Maritime to provide the current depth of the trawl sensor.

### Format

```
@IIDBS,,,x.x,M,,<CR><LF>
```

### Description

- 1 **II**: Talker identifier
- 2 **DBS**: Datagram identifier
- 3 **x.x,M**: Depth (Metres) (0 - 2000)

### Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Proprietary datagram formats, page 46](#)

## Simrad GLL datagram format

Simrad GLL is a proprietary datagram format created by Kongsberg Maritime to provide the current geographical position of the trawl sensor.

### Note

*The GLL datagram may be received from integrated instruments using the “ii” talker identifier. The Simrad ITI system uses the same talker identifier “ii”, and this has caused some confusion. In order to rectify this, the ITI GLL datagram has been deactivated.*

### Format

```
$IIIGLLddmm.hh,N,ddmmhh,ss,A<CR><LF>
```

### Description

- 1 **II:** Talker identifier
- 2 **GLL:** Datagram identifier
- 3 **ddmm.hh,N:** Latitude (degrees, minutes and hundredths)
  - **N** = North
  - **S** = South
- 4 **ddmm.hh,W:** Longitude (degrees, minutes and hundredths)
  - **W** = West
  - **E** = East
- 5 **A:** Status

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[Proprietary datagram formats, page 46](#)

## Simrad HB2 datagram format

Simrad HB2 is a proprietary datagram format created by Kongsberg Maritime. It provides the vertical distance from the headrope to the footrope (opening), and from the headrope to the bottom (height). It is used for the second trawl in a dual trawl system. The heights are measured by an ITI TrawlEye or a height sensor.

### Format

```
@IIHB2,x.x,M,y.y,M<CR><LF>
```

## Description

- 1 **II:** Talker identifier
- 2 **HB2:** Datagram identifier
- 3 **x.x,M:** This is the distance (height) from the headrope to the footrope. (0 - 100 m)
- 4 **y.y, M:** This is the distance (height) from headrope to bottom (seabed). (0 - 100 m)

Tip

---

*The information from the sensor on the first trawl is provided in the Simrad HFB datagram.*

---

## Related topics

- [Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Proprietary datagram formats, page 46](#)

## Simrad HFB datagram format

Simrad HFB is a proprietary datagram format created by Kongsberg Maritime. It provides the vertical distance from the headrope to the footrope (opening), and from the headrope to the bottom (height). The heights are measured by an ITI TrawlEye or a height sensor.

## Format

```
@IIHFB,x.x,M,y.y,M<CR><LF>
```

## Description

- 1 **II:** Talker identifier
- 2 **HFB:** Datagram identifier
- 3 **x.x,M:** This is the distance (height) from the headrope to the footrope. (0 - 100 m)
- 4 **y.y, M:** This is the distance (height) from headrope to bottom (seabed). (0 - 100 m)

Tip

---

*If you use two height sensors, the information from the second sensor is provided in the Simrad HB2 datagram.*

---

## Related topics

- [Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Proprietary datagram formats, page 46](#)

## Simrad MTW datagram format

Simrad MTW is a proprietary datagram format created by Kongsberg Maritime to provide the water temperature measured by the trawl sensor.

### Format

```
$IIMTW,xx.x,C<CR><LF>
```

#### Description

- 1 **I**: Talker identifier
- 2 **MTW**: Datagram identifier
- 3 **xx.x,C**: Water temperature (Degrees, Celsius)

#### Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Proprietary datagram formats, page 46](#)

## Simrad TDS datagram format

Simrad TDS is a proprietary datagram format created by Kongsberg Maritime to provide the door spread. That is the distance between the two trawl doors.

### Format

```
@IITDS,x.x,M<CR><LF>
```

#### Description

- 1 **I**: Talker identifier
- 2 **TDS**: Datagram identifier
- 3 **x.x,M**: Distance (metres)

#### Note

*In a dual trawl system, the distance between the second door set is provided in the Simrad TS2 datagram.*

#### Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Proprietary datagram formats, page 46](#)

## Simrad TFI datagram format

Simrad TFI is a proprietary datagram format created by Kongsberg Maritime to provide the status information from maximum three catch sensors.

### Format

```
@IITFI,x,y,z<CR><LF>
```

### Description

- 1 **II:** Talker identifier
- 2 **TFI:** Datagram identifier
- 3 **x:** Status #1
  - **0** = Off
  - **1** = On
  - **2** = No answer
- 4 **y:** Status #2
  - **0** = Off
  - **1** = On
  - **2** = No answer
- 5 **z:** Status#3
  - **0** = Off
  - **1** = On
  - **2** = No answer

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[Proprietary datagram formats, page 46](#)

## Simrad TPC datagram format

Simrad TPC is a proprietary datagram format created by Kongsberg Maritime to provide the trawl position in Cartesian coordinates.

### Format

```
@IITPC,x,M,y,M,z,M<CR><LF>
```

## Description

- 1 **II:** Talker identifier
- 2 **TPC:** Datagram identifier
- 3 **x,M:** This is the horizontal distance in metres from the vessel's centre line.
- 4 **y,M:** This is the horizontal distance in metres from the transducer to the trawl along the vessel's centre line.
- 5 **z,M:** This is the depth in metres of the trawl below the water surface.

## Related topics

- [Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Proprietary datagram formats, page 46](#)

## Simrad TPR datagram format

Simrad TPR is a proprietary datagram format created by Kongsberg Maritime. It provides the relative bearing and water depth of the trawl sensor, as well as its distance from the vessel. The bearing resolution is 1 degree.

### Format

```
@IITPR,x,M,y,P,z,z,M<CR><LF>
```

## Description

Note \_\_\_\_\_

*All data relate to the trawl sensor (target).*

- 
- 1 **II:** Talker identifier
  - 2 **TPR:** Datagram identifier
  - 3 **x,M:** Horizontal range (Metres) (0 – 4000)
  - 4 **y,P:** Bearing (degrees) (Relative to vessel heading)
  - 5 **z,z,M:** Depth (Metres) (0 - 2000)

Note \_\_\_\_\_

*The Simrad ITI measures the depth differently from the range and the bearing. If the ITI only knows the range and the bearing, the depth field is empty.*

## Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Proprietary datagram formats, page 46](#)

## Simrad TPT datagram format

Simrad TPT is a proprietary datagram format created by Kongsberg Maritime to provide the true bearing and water depth of the trawl sensor, as well as its distance from the vessel. The bearing resolution is 1 degree.

### Format

```
@IITPT,x,M,y,P,z.z,M<CR><LF>
```

### Description

Note \_\_\_\_\_

*All data relate to the trawl sensor (target).*

- 
- 1   **I**I: Talker identifier
  - 2   **TPT**: Datagram identifier
  - 3   **x,M**: Horizontal range (Metres) (0 - 4000)
  - 4   **y,P**: Bearing (degrees) (True)
  - 5   **z,z,M**: Depth (Metres) (0 - 2000)

Note \_\_\_\_\_

*The Simrad ITI measures the depth differently from the range and the bearing. If the ITI only knows the range and the bearing, the depth field is empty.*

---

## Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Proprietary datagram formats, page 46](#)

## Simrad TS2 datagram format

Simrad TS2 is a proprietary datagram format created by Kongsberg Maritime to provide the door spread in a dual trawl system. That is the distance between the two trawl doors.

### Format

```
@IITS2,x.x,M<CR><LF>
```

#### Description

- 1 **II:** Talker identifier
- 2 **TS2:** Datagram identifier
- 3 **x.x,M:** Distance (Metres)

#### Note

*The distance between the first door set is provided in datagram Simrad TDS.*

#### Related topics

- [Supported datagram formats, page 12](#)
- [Datagram formats, page 24](#)
- [Proprietary datagram formats, page 46](#)

## Simrad TTS datagram format

Simrad TTS is a proprietary datagram format created by Kongsberg Maritime. It provides the distance between the trawl sensor and the shoal.

### Format

```
@IITTS,x,M,y,M,z,M<CR><LF>
```

#### Description

- 1 **II:** Talker identifier
- 2 **TTS:** Datagram identifier
- 3 **x,M:** This is the horizontal distance in metres from the trawl to the shoal in a direction normal to the vessel's centre line.
- 4 **y,M:** This is the horizontal distance in metres from the trawl to the shoal in the direction of the vessel's centre line.
- 5 **z,M:** This is the vertical distance (height) in metres from the trawl to the shoal.

## Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Proprietary datagram formats, page 46](#)

## Simrad MDS datagram format

Simrad MDS is a proprietary datagram format created by Kongsberg Maritime. It contains the location, bearing and depth of a tracked target. All information is presented relative to your own vessel. All data are related to the tracked target.

### Format

```
$PSIMMDS, hh:mm:ss, dd:mm:yy, aaaa, A, llll.lll, a,  
yyyyy.yyy, a, xxx (+), M, ppp, P, zzz (+), M, vvv.v, N,  
ttt, D, www (+), A, ddd (+), A*hh<CR><LF>
```

### Description

- 1 **SPSIM:** Talker identifier
- 2 **MDS:** Datagram identifier
- 3 **hh:mm:ss:** Coordinated Universal Time (UTC)
- 4 **dd:mm:yy:** Date (Day, month and year)
- 5 **aaaa:** Target identification

These four characters contain the target identifier on the format AT X, where X is an integer defining the target number. The sonar system will export information from maximum three tracked targets simultaneously.

- If one target is tracked, one datagram is exported.
  - If two targets are tracked, two consecutive datagrams are exported.
  - If three targets are tracked, three consecutive datagrams are exported.
  - If a fourth target is selected, the information about the first (oldest) target is disabled.
- 6 **A:** Status
    - **V:** The information is valid.
    - **N:** The information is not valid.
  - 7 **llll.lll,a:** Latitude (Degrees, minutes and hundredths)
    - **N:** North
    - **S:** South
  - 8 **yyyyy.yyy,a:** Longitude (Degrees, minutes and hundredths)

- **W:** West
  - **E:** East
- 9 **xxx(+),M:** Horizontal range (Metres)  
 An empty denomination field indicates an invalid value. This field has a variable length that must contain minimum three digits.
- 10 **ppp,P:** Direction to target in degrees, relative to north  
 An empty denomination field indicates an invalid value.
- 11 **zzz(+),M:** Depth (Metres)  
 An empty denomination field indicates an invalid value. This field has a variable length that must contain minimum three digits.
- 12 **vv.v,N:** Speed (knots)  
 An empty denomination field indicates an invalid value.
- 13 **ttt,D:** Course (degrees)  
 An empty denomination field indicates an invalid value.
- 14 **www(+),A:** Area in square metres  
 An empty denomination field indicates an invalid value. This field has a variable length that must contain minimum three digits.
- 15 **ddd(+),A:** Volume in tonnes  
 An empty denomination field indicates an invalid value. This field has a variable length that must contain minimum three digits.
- 16 **\*hh:** Checksum

### Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Proprietary datagram formats, page 46](#)

## Simrad TPP datagram format

Simrad TPP is a proprietary datagram format created by Kongsberg Maritime. It exports the horizontal range, bearing and depth of a tracked target. All data are related to the tracked target.

### Format

```
@SSTPP,xxxx,M,yyy,P,zzzz,M,nn<CR><LF>
```

### Description

- 1 **SS:** Talker identifier

- 2 **TPP:** Datagram identifier
- 3 **xxxx,M:** Horizontal range (Metres)
- 4 **yyy,P:** Bearing (degrees) (Relative to vessel heading)
- 5 **zzzz,M:** Depth (Metres)
- 6 **nn:** Target identification
  - **00:** An echo target is tracked.
  - **10:** A position is tracked.
  - **20 – 29:** Markers 0 to 9 are tracked.

Position datagrams for markers are not exported.

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[Proprietary datagram formats, page 46](#)

## Kongsberg EM Attitude 3000 datagram format

The Kongsberg EM Attitude 3000 is a proprietary datagram format created by Kongsberg Maritime for use with digital motion sensors. It holds roll, pitch, heave and heading information. The datagram contains a 10-byte message.

### Format

Data description	Example	Format	Valid range
Sync byte 1 / Sensor status [1]	90h to Afh = sensor status	1U	00h, 90h to Afh
Sync byte 2	Always 90h	1U	144
Roll LSB [2]		1U	
Roll MSB [2]		1U	
Pitch LSB [2]		1U	
Pitch MSB [2]		1U	
Heave LSB [2]		1U	
Heave MSB [2]		1U	
Heading LSB [2]		1U	
Heading MSB [2]		1U	

### Description

**LSB** = least significant byte

**MSB** = most significant byte.

#### 1 Sync byte 1 / Sensor status

- **00h:** This value is sync byte 1.

- **90h**: This value indicates valid measurements with full accuracy.
- Any value from **91h** to **99h** indicates valid data with reduced accuracy (decreasing accuracy with increasing number).
- Any value from **9Ah** to **9Fh** indicates non-valid data but normal operation (for example configuration or calibration mode).
- Any value from **A0h** to **AFh** indicates a sensor error status.

## 2 All data are in 2's complement binary.

Resolution is 0.01 degrees for roll, pitch and heading, and 1 cm for heave.

- Roll is positive with port side up with valid range  $\pm 179.99$  degrees.
- Pitch is positive with bow up with valid range  $\pm 179.99$  degrees.
- Heave is positive up with valid range  $\pm 9.99$  m.
- Heading is positive clockwise with valid range 0 to 359.99 degrees.

If a value is outside the valid range, it is assumed to be non-valid, and rejected.

### Note

---

*Heave is logged as positive downwards (the sign is changed) including roll and pitch induced lever arm translation to the transmit transducer.*

---

You can define how roll is assumed to be measured, either with respect to the horizontal plane (the *Hippy 120* or *TSS* convention), or to the plane tilted by the given pitch angle (i.e. as a rotation angle around the pitch tilted forward pointing x-axis).

The latter convention (called *Tate-Bryant* in the POS/MVdocumentation) is used inside the system in all data displays and in the logged data. A transformation is applied if the roll is given with respect to the horizontal.

### Note

---

*This format was originally designed for use with the early multibeam echo sounders manufactured by Kongsberg Maritime. In the original version of the format (Kongsberg EM Attitude 1000), the first synchronisation byte was always assumed to be zero. The sensor manufacturers were then requested to include sensor status in the format using the first synchronisation byte for this purpose.*

---

## Related topics

- [Supported datagram formats, page 12](#)
- [Datagram formats, page 24](#)
- [Proprietary datagram formats, page 46](#)

## KM Binary datagram format

KM Binary is a proprietary datagram format created by Kongsberg Maritime for general use.

### Format

Data description	Unit of measurement	Format	No. of bytes
Start ID	#KMB	char	4U
Datagram length		uint16	2U
Datagram version (=1)		uint16	2U
UTC seconds	s	uint32	4U
UTC nanoseconds	ns	uint32	4U
Status		uint32	4U
Latitude	deg	double	8F
Longitude	deg	double	8F
Ellipsoid height	m	float	4F
Roll	deg	float	4F
Pitch	deg	float	4F
Heading	deg	float	4F
Heave	m	float	4F
Roll rate	deg/s	float	4F
Pitch rate	deg/s	float	4F
Yaw rate	deg/s	float	4F
North velocity	m/s	float	4F
East velocity	m/s	float	4F
Down velocity	m/s	float	4F
Latitude error	m	float	4F
Longitude error	m	float	4F
Height error	m	float	4F
Roll error	deg	float	4F
Pitch error	deg	float	4F
Heading error	deg	float	4F
Heave error	m	float	4F
North acceleration	m/s <sup>2</sup>	float	4F
East acceleration	m/s <sup>2</sup>	float	4F
Down acceleration	m/s <sup>2</sup>	float	4F
<b>Delayed heave:</b>			
UTC seconds	s	uint32	4U

Data description	Unit of measurement	Format	No. of bytes
UTC nanosecond	ns	uint32	4U
Delayed heave	m	float	4F

### Description

Data format	Little endian (the least significant byte is transmitted first). Float is according to IEEE - 754.
Datagram length	The total number of bytes in the datagram
Datagram version	The version is incremented if the datagram format is changed.
Timestamp format	Epoch 1970-01-01 UTC time
Position and height	At user-defined sensor reference point. Position in decimal degrees. <ul style="list-style-type: none"> <li>• Latitude: Negative on Southern hemisphere</li> <li>• Longitude: Negative on Western hemisphere</li> <li>• Height: Positive above ellipsoid</li> </ul>
Positive roll	Port side up
Positive pitch	Bow up
Positive heave	Downwards, at user-defined sensor reference point
	True north
Error fields	Sensor data quality: RMS -1= not implemented

### Status

One bit per status info, 1= active

Bit	
	<b>Invalid data:</b>
0	Horizontal position and velocity
1	Roll and pitch
2	
3	Heave and vertical velocity
4	Acceleration
5	Delayed heave
	<b>Reduced performance:</b>
16	Horizontal position and velocity
17	Roll and pitch
18	
19	Heave and vertical velocity

Bit	
20	Acceleration
21	Delayed heave

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[Proprietary datagram formats, page 46](#)

# Third-party datagram formats

## Topics

- [AML Sound speed datagram format, page 67](#)
- [Trimble PTNL,GGK datagram format, page 69](#)
- [Furuno GPhve datagram format, page 70](#)
- [Furuno GPatt datagram format, page 71](#)
- [Hemisphere GNSS GPHEV datagram format, page 72](#)
- [Teledyne TSS1 datagram format, page 72](#)
- [Serge BSC datagram format, page 74](#)
- [Ryokusei RBY datagram format, page 75](#)

## AML Sound speed datagram format

AML is a third-party proprietary datagram format created by AML Oceanographic (<http://www.amloceanographic.com>) for use with their sound velocity probes.

### Note

---

*The datagram format described here remains the property of the organization that defined it. If you need more information, contact the owner.*

---

The sound velocity probe output is configurable. The code is searching for a value between 1300 and 1800 and uses it as the sound speed.

The following input data formats are supported by the AML sound velocity probe:

### Format

```
xxxx.x<CR><LF>
```

### Description

- xxxx.x: Sound speed

### Format

```
±xxx.xx yyyy.y<CR><LF>
```

## Description

- 1 **±xxx.xx**: Not used
- 2 **yyy.y**: Sound speed

## Format

```
dd/mm/yy hh:mm:ss:ms yyy.yy xxxx.xx
```

## Description

- 1 **dd/mm/yy**: Not used
- 2 **hh:mm:ss:ms**: Not used
- 3 **yyy.yy**: Not used
- 4 **xxxx.xx**: Sound speed

## Format

```
dd/mm/yy hh:mm:ss:ms xxxx.xx nn.nnn
```

## Description

- 1 **dd/mm/yy**: Not used
- 2 **hh:mm:ss:ms**: Not used
- 3 **xxxx.xx**: Sound speed
- 4 **nn.nnn**: Temperature

## Format

```
dd/mm/yy hh:mm:ss:ms yyy.yy xxxx.xx nn.nnn
```

## Description

- 1 **dd/mm/yy**: Not used
- 2 **hh:mm:ss:ms**: Not used
- 3 **yyy.yy**: Not used
- 4 **xxxx.xx**: Sound speed
- 5 **nn.nnn**: Temperature

## Related topics

- [Supported datagram formats, page 12](#)
- [Datagram formats, page 24](#)
- [Third-party datagram formats, page 67](#)

## Trimble PTNL,GGK datagram format

PTNL ,GGK is a proprietary datagram from Trimble (<https://www.trimble.com>). The PTNL, GGK datagram is used to decode the time, position, type and dilution of precision of the current position.

### Format

```
$PTNL,GGK,hhmmss.ss,ddmmyy,dddmm.mmmmmmmm,a,dddmm.mmmmmmmmm,a,x,zz,w.w,EHTaaa.bbb,M*hh
```

### Description

#### Note

*The datagram format described here remains the property of the organization that defined it. This datagram description is not complete. If you need more information, contact the owner.*

- 1 **\$PTNL:** Talker identifier
- 2 **GGK:** Datagram identifier
- 3 **hhmmss.ss:** Coordinated Universal Time (UTC) of the current position
- 4 **ddmmyy:** Day, month and year
- 5 **dddmm.mmmmmmmmm:** Latitude (degrees)
- 6 **a:** Direction of latitude
  - **N** = North
  - **S** = South
- 7 **dddmm.mmmmmmmmm:** Longitude (degrees)
- 8 **a:** Direction of longitude
  - **E** = East
  - **W** = West
- 9 **x:** GPS quality indicator ()
- 10 **zz:** Number of satellites in use (00 - 12) (The number of satellites may be different from the number in view.)
- 11 **w.w:** PDOP (Position dilution of precision)
- 12 **EHTaaa.bbb:** Ellipsoidal height of fix
- 13 **M:** Ellipsoid height (metres)
- 14 **\*hh:** Checksum

Note \_\_\_\_\_

*The PTNL, GGK datagram is longer than the NMEA-0183 standard of 80 characters.  
The latitude and longitude are in the datum and ellipsoid of the selected reference frame.*

---

## GPS quality indicator

Quality indicator 0 (zero) means that fix is not available or invalid. Other values:

- 1 Autonomous GPS fix
- 2 Differential, floating carrier phase integer-based solution, RTK (float)
- 3 Differential, fixed carrier phase integer-based solution, RTK (fixed)
- 4 Differential, code phase only solution (DGPS)
- 5 WAAS corrected differential position
- 6 RTK network position (float solution)
- 7 RTK network position (fixed solution)

## Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[Third-party datagram formats, page 67](#)

## Furuno GPhve datagram format

Furuno GPhve is a proprietary datagram format created by Furuno (<http://www.furuno.jp>) to contain heave information.

Note \_\_\_\_\_

*The datagram format described here remains the property of the organization that defined it. If you need more information, contact the owner.*

---

## Format

```
$PFEC,GPhve,xx.xxx,A*hh<CR><LF>
```

## Description

- 1 **\$PFEC**: Talker identifier
- 2 **GPhve**: Datagram identifier
- 3 **xx.xxx**: Heave (Metres)
- 4 **A**: Status
- 5 **\*hh**: Checksum

## Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Third-party datagram formats, page 67](#)

## Furuno GPatt datagram format

Furuno GPatt is a proprietary datagram format created by Furuno (<http://www.furuno.jp>) to contain pitch, roll and yaw information.

### Note

---

*The datagram format described here remains the property of the organization that defined it. If you need more information, contact the owner.*

---

## Format

The datagram is available in two versions.

### Version 1.5

```
$PFEC,GPatt,xxx.x,yy.y,zz.z<CR><LF>
```

### Version 2.0

```
$PFEC,GPatt,xxx.x,yy.y,zz.z*hh<CR><LF>
```

## Description

- 1 **\$PFEC**: Talker identifier
- 2 **GPatt**: Datagram identifier
- 3 **xxx.x**: Yaw (degrees)
- 4 **yy.y**: Pitch (degrees)
- 5 **zz.z**: Roll (degrees)
- 6 **\*hh**: Checksum

## Related topics

[Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Third-party datagram formats, page 67](#)

## Hemisphere GNSS GPHEV datagram format

GPHEV is a proprietary datagram format created by Hemisphere GNSS (<https://hemispherengnss.com>) to contain heave information.

### Note

---

*The datagram format described here remains the property of the organization that defined it. If you need more information, contact the owner.*

---

### Format

```
$GPHEV,H,*hh<CR><LF>
```

### Description

- 1    \$: Talker identifier
- 2    **GPHEV**: Datagram identifier
- 3    H: Heave (Metres)
- 4    \***hh**: Checksum

### Related topics

- [Supported datagram formats, page 12](#)  
[Datagram formats, page 24](#)  
[Third-party datagram formats, page 67](#)

## Teledyne TSS1 datagram format

Teledyne TSS1 is a proprietary datagram format created by Teledyne TSS Navigation Systems for heave, roll and pitch compensation. When you select this protocol, the number of sensor variables is fixed, and there is no token associated with it.

### Format

```
:aabbbb shhhhX srrrr spppp<CR><LF>
```

### Description

The format is based on ASCII characters, the datagram has a fixed length, and it is terminated with a carriage return and line feed. Baud rate and output rate may be adjusted to fit your needs. The definition of the attitude angles in this format is different from the *Euler* angles definition used elsewhere. The difference appears in the roll angle, where:

$$\text{Roll}_{\text{echo sounder}} = \arcsin [\sin(\text{Roll}_{\text{Euler}}) \times \cos(\text{Pitch}_{\text{Euler}})]$$

1 **aa:** Sway acceleration

This is a dual-character hex number. The value is provided as 0.03835 m/ss units.

2 **bbbb:** Heave acceleration

This is a four-character hex number. The value is provided as 0.000625 m/ss units.

3 **s:** This is a single character.

If the value is positive, a "space" character is provided.

If the value is negative, a "–" character is provided.

4 **hhhh:** Heave position

This is a four-character decimal number. The value is given in centimetres. Positive value is Up.

5 **x:** Status

- **U:** Unaided mode/Stable data

The sensor operates without external input data.

- **u:** Unaided mode/Unstable data

The sensor operates without external input data. However, the data from the sensor is unstable. A probable cause for this is the lack of alignment after the sensor has been switched on or restarted. The alignment period from a power recycle is normally approximately five minutes.

- **G:** Speed aided mode/Stable data

The sensor operates with external input of speed data.

- **g:** Speed aided mode/Unstable data

The sensor operates with external input of speed data. However, the data from the sensor is unstable. A probable cause for this is the lack of alignment after the sensor has been switched on or restarted. It can also be a failure in the data input.

- **H:** Heading aided mode/Stable data

The sensor operates with external input of heading data.

- **h:** Heading aided mode/Unstable data

The sensor operates with external input of heading data. However, the data from the sensor is unstable. A probable cause for this is the lack of alignment after the sensor has been switched on or restarted. It can also be a failure in the data input.

- **F:** Full aided mode/Stable data

The sensor operates with external input of both speed and heading data.

- **f:** Full aided mode/Unstable data

The sensor operates with external input of both speed and heading data.

However, the data from the sensor is unstable. A probable cause for this is the lack of alignment after the sensor has been switched on or restarted. It can also be a failure in the data input.

- 6 **s**: This is a single character.  
If the value is positive, a "space" character is provided.  
If the value is negative, a "--" character is provided.
- 7 **rrrr**: Roll angle  
This is a four-character decimal number. The value is given in hundredths of a degree.
- 8 **s**: This is a single character.  
If the value is positive, a "space" character is provided.  
If the value is negative, a "--" character is provided.
- 9 **pppp**: Pitch angle  
This is a four-character decimal number. The value is given in hundredths of a degree.

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[Third-party datagram formats, page 67](#)

## Serpe BSC datagram format

Serpe BSC is a proprietary datagram format created by Serpe. It is supplied with buoys and provides the geographical location of the buoy as well as the water temperature the buoy measures.

### Note

---

*The datagram format described here remains the property of the organization that defined it. If you need more information, contact the owner.*

---

### Format

```
$??BSC,bbbb,1111.11,n,wwwww.ww,W,  
tt.t,vv,dd.dd.hh,xx.xx.xx<CR><LF>
```

### Description

- 1 **??**: Talker identifier
- 2 **BSC**: Datagram identifier
- 3 **bbbb**: This is the number (identification) of the buoy.
- 4 **1111.11,n**: Latitude

- **N** = North
- **S** = South

The information is provided in degrees with decimals. 0222.17 corresponds to 2°13.302'. 0220.50 corresponds to 2°12.3'.

5 **wwww.ww,W**: Longitude

- **W** = West
- **E** = East

The information is provided in degrees with decimals.

6 **tt.t**: Water temperature (Degrees Celsius )

7 **vv**: Battery voltage

8 **dd.dd.hh**: Day, month and year

9 **xx.xx.xx**: Not used

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[Third-party datagram formats, page 67](#)

## Ryokusei RBY datagram format

Ryokusei RBY is a proprietary datagram format created by Ryokusei. It is supplied with buoys and provides the geographical location of the buoy as well as the water temperature the buoy measures. The datagram also provides echo sounder information.

### Note

*The datagram format described here remains the property of the organization that defined it. If you need more information, contact the owner.*

### Format

```
$PRBY,xxx,hmmss,1111.ll,a,yyyyyy.yy,a,
yyymmdd,tt.t,a0b0c0d0e0f0g0h0i0,BB.B<CR><LF>
```

### Description

- 1 **\$P**: Talker identifier
- 2 **RBY**: Datagram identifier
- 3 **xxx**: This is the number (identification) of the buoy.
- 4 **hhmmss**: Time (Hours, minutes and seconds)
- 5 **1111.ll,a**: Latitude (Degrees, minutes and hundredths)

- **N** = North
  - **S** = South
- 6 **yyyyy.yyy,a**: Longitude (Degrees, minutes and hundredths)  
• **W** = West  
• **E** = East
- 7 **yyymmdd**: Date (Year, month and day)
- 8 **tt.t**: Water temperature (Degrees Celsius) (0 – 35.5 °C)
- 9 **a0b0c0d0e0f0g0h0i0**: Echo sounder data
- 10 **BB.B**: Battery voltage

### Related topics

[Supported datagram formats, page 12](#)

[Datagram formats, page 24](#)

[Third-party datagram formats, page 67](#)

# File formats

## Topics

[NetCDF file format, page 78](#)

## NetCDF file format

NetCDF (Network Common Data Form) is a data model, API library (application programming interface) and a file format. It is used for storing and managing data. NetCDF is developed and maintained by Unidata. Unidata is part of the US University Corporation for Atmospheric Research (UCAR) Community Programs (UCP). Unidata is funded by the US National Science Foundation.

SONAR-NetCDF4 is a data and metadata convention for storage of data from active sonars in NetCDF4 formatted files, defined by The International Council for the Exploration of the Sea (ICES). Sonar-NetCDF4 consists primarily of a naming convention and a data structure within the NetCDF4 data model.

NetCDF output requires a dedicated software license.

See our website for more information.

- <https://www.kongsberg.com/fisherysonar>

### Note

---

*The data files will normally become very large. If you wish to record large amounts of data, make sure that you have enough space on your hard disk. Unless your computer is equipped with a very large disk, we recommend that you save the data to an external storage device.*

*The requirement for data storage is from 15 to 50 Gb per hour, depending on your operating modes and settings.*

---

## Related functionality

### Processed Data to File page

The sonar system can export several types of processed data file formats. Use **Processed Data to File** to define which processed data formats to save, and where to place the files. This page is located in the **Output** dialog box. To open, select it on the **Operation** menu.

### Software License page

The sonar system does not need any software licenses to operate. However, specific software license codes "unlocks" additional functionality. The **Software License** settings allow you to type a license code (text string) to unlock these optional functions.

This page is located in the **Installation** dialog box. To open the page, select **Installation** on the **Setup** menu.

# Index

## A

about	
document downloads	7
NMEA 0183	26
NMEA datagram formats	25
online information	7
registered trademarks	7
software license	7
software version	7
Standard NMEA 0183 communication	
parameters	27
target audience	7
this publication	7
About the NMEA datagram formats	25
AML Sound speed datagram format	67
AMLSoundspeed	
datagram format	67
annotation	
datagram format	46
annotation data	
datagram formats	13
ATS	
datagram format	46
ATS Annotation	
datagram format	46
ATS Annotation datagram format	46

## B

BSC	
datagram format	74

## C

catch monitoring sensor information	
datagram formats	18
communication parameters	
NMEA 0183	27
CUR	
datagram format	28

## D

DAD	
datagram format	52
datagram format	
AMLSoundspeed	67
ATS	46
ATS Annotation	46
BSC	74
CUR	28
DAD	52
DBS	30, 52
DBT	30
DDC	31
DPT	32
EM Attitude 3000	62
Furuno GPatt	71
Furuno GPhve	70
GGA	33

GGK	34
GLL	35, 53
GPatt	71
GPHEV	72
GPhve	70
HB2	53
HDG	35
HDM	36
HDT	37
Hemisphere GNSS GPHEV	72
HFB	54
KM Binary	64
Kongsberg EM Attitude 3000	62
MDS (Measured Data Shoal)	60
Motion EM3000	62
MTW	37, 55
MWD	38
MWV	38
NMEA CUR	28
NMEA DBS	30
NMEA DBT	30
NMEA DDC	31
NMEA DPT	32
NMEA GGA	33
NMEA GGK	34
NMEA GLL	35
NMEA HDG	35
NMEA HDM	36
NMEA HDT	37
NMEA MTW	37
NMEA MWD	38
NMEA MWV	38
NMEA RMC	39
NMEA THS	40
NMEA TLL	40
NMEA VBW	41
NMEA VHW	42
NMEA VTG	43
NMEA VWR	44
NMEA ZDA	44
PSIMP,C	47
PSIMP,D	49
PSIMP,F	51
PTNL,GGK	69
RBY	75
RMC	39
Ryokusei RBY	75
Serpé BSC	74
Simrad DAD	52
Simrad DBS	52
Simrad GLL	53
Simrad HB2	53
Simrad HFB	54
Simrad MTW	55
Simrad PSIMP,C	47
Simrad PSIMP,D	49
Simrad PSIMP,F	51
Simrad TDS	55
Simrad TFI	56
Simrad TPC	56

Simrad TPR.....	57
Simrad TPT.....	58
Simrad TS2.....	59
Simrad TTS.....	59
TDS.....	55
Teledyne TSS1.....	72
TFI.....	56
THS.....	40
TLL.....	40
TPC.....	56
TPP (Tracked Target Position).....	61
TPR.....	57
TPT.....	58
Trimble PTNL,GGK.....	69
TS2.....	59
TTS.....	59
VBW.....	41
VHW.....	42
VTG.....	43
VWR.....	44
ZDA.....	44
datagram formats	
annotation data.....	13
catch monitoring sensor information.....	18
depth information.....	14
external objects.....	21
GPS (Global Positioning System).....	14
gyro compass.....	15
heading sensor.....	15
markers.....	23
motion sensor.....	22
NMEA.....	25
palette.....	21
positioning system.....	14
sound speed.....	18
speed log.....	19
target markers.....	23
temperature.....	20
trawl information.....	16
wind direction.....	20
wind speed.....	20
DBS	
datagram format.....	30, 52
DBT	
datagram format.....	30
DDC	
datagram format.....	31
depth information	
datagram formats .....	14
description	
MDS (Measured Data Shoal) (datagram format).....	60
NetCDF file format.....	78
Simrad MDS datagram format.....	60
Simrad TPP datagram format .....	61
TPP (Tracked Target Position) (datagram format).....	61
documentation	
downloading.....	7
downloading documentation.....	7
DPT	
datagram format.....	32
<b>E</b>	
EM Attitude 3000	
datagram format.....	62
external objects	
datagram formats .....	21
<b>F</b>	
file format	
NetCDF .....	78
Furuno GPatt	
datagram format.....	71
Furuno GPatt datagram format.....	71
Furuno GPhve	
datagram format.....	70
Furuno GPhve datagram format .....	70
<b>G</b>	
GGA	
datagram format.....	33
GGK	
datagram format.....	34
GLL	
datagram format.....	35, 53
Global Positioning System (GPS)	
datagram formats .....	14
GPatt	
datagram format.....	71
GPHEV	
datagram format.....	72
GPhve	
datagram format.....	70
GPS (Global Positioning System)	
datagram formats .....	14
gyro compass	
datagram formats .....	15
<b>H</b>	
HB2	
datagram format.....	53
HDG	
datagram format.....	35
HDM	
datagram format.....	36
HDT	
datagram format.....	37
heading sensor	
datagram formats .....	15
help	
support .....	9
technical support .....	9
Hemisphere GNSS GPHEV	
datagram format.....	72
Hemisphere GNSS GPHEV datagram format .....	72
HFB	
datagram format.....	54
<b>I</b>	
information	
support .....	9
technical support .....	9

Inputs .....	13
<b>K</b>	
KM Binary	
datagram format.....	64
KM Binary datagram format .....	64
Kongsberg EM Attitude 3000	
datagram format.....	62
Kongsberg EM Attitude 3000 datagram format .....	62
Kongsberg Maritime	
support .....	9
<b>L</b>	
license information	
software .....	7
logo	
registered trademark.....	7
<b>M</b>	
markers	
datagram formats .....	23
MDS (Measured Data Shoal)	
description (datagram format).....	60
Motion EM3000	
datagram format.....	62
Motion Reference Unit (MRU)	
datagram formats .....	22
motion sensor	
datagram formats .....	22
MRU (Motion Reference Unit)	
datagram formats .....	22
MTW	
datagram format.....	37, 55
MWD	
datagram format.....	38
MWV	
datagram format.....	38
<b>N</b>	
NetCDF	
file format.....	78
NetCDF file format	
description .....	78
NMEA	
0183 .....	26
datagram formats .....	25
NMEA 0183	
about.....	26
communication parameters .....	27
NMEA sentence structure .....	26
NMEA CUR	
datagram format.....	28
NMEA CUR datagram format .....	28
NMEA datagram formats	
about.....	25
NMEA DBS	
datagram format.....	30
NMEA DBS datagram format .....	30
NMEA DBT	
datagram format.....	30
NMEA DBT datagram format .....	30
NMEA DDC	
datagram format.....	31
NMEA DDC datagram format .....	31
NMEA DPT	
datagram format.....	32
NMEA DPT datagram format .....	32
NMEA GGA	
datagram format.....	33
NMEA GGA datagram format .....	33
NMEA GGK	
datagram format.....	34
NMEA GGK datagram format .....	34
NMEA GLL	
datagram format.....	35
NMEA GLL datagram format .....	35
NMEA HDG	
datagram format.....	35
NMEA HDG datagram format .....	35
NMEA HDM	
datagram format.....	36
NMEA HDM datagram format .....	36
NMEA HDT	
datagram format.....	37
NMEA HDT datagram format .....	37
NMEA MTW	
datagram format.....	37
NMEA MTW datagram format .....	37
NMEA MWD	
datagram format.....	38
NMEA MWD datagram format .....	38
NMEA MWV	
datagram format.....	38
NMEA MWV datagram format .....	38
NMEA RMC	
datagram format.....	39
NMEA RMC datagram format .....	39
NMEA sentence structure	
NMEA 0183 .....	26
NMEA THS	
datagram format.....	40
NMEA THS datagram format .....	40
NMEA TLL	
datagram format.....	40
NMEA TLL datagram format .....	40
NMEA VBW	
datagram format.....	41
NMEA VBW datagram format .....	41
NMEA VHW	
datagram format.....	42
NMEA VHW datagram format .....	42
NMEA VTG	
datagram format.....	43
NMEA VTG datagram format .....	43
NMEA VWR	
datagram format.....	44
NMEA VWR datagram format .....	44
NMEA ZDA	
datagram format.....	44
NMEA ZDA datagram format .....	44
<b>O</b>	
offices	
support .....	9

technical support.....	9
online information	
about.....	7
website .....	7
Outputs .....	23
 <b>P</b>	
palette	
datagram formats .....	21
positioning system	
datagram formats .....	14
PSIMP,C	
datagram format.....	47
PSIMP,D	
datagram format.....	49
PSIMP,F	
datagram format.....	51
PTNL,GGK	
datagram format.....	69
purpose	
this publication .....	7
 <b>R</b>	
RBY	
datagram format.....	75
registered trademarks.....	7
RMC	
datagram format.....	39
Ryokusei RBY	
datagram format.....	75
Ryokusei RBY datagram format.....	75
 <b>S</b>	
Serpe BSC	
datagram format.....	74
Serpe BSC datagram format.....	74
Simrad	
registered trademark.....	7
support .....	9
SIMRAD	
registered trademark.....	7
Simrad DAD	
datagram format.....	52
Simrad DAD datagram format.....	52
Simrad DBS	
datagram format.....	52
Simrad DBS datagram format.....	52
Simrad GLL	
datagram format.....	53
Simrad GLL datagram format.....	53
Simrad HB2	
datagram format.....	53
Simrad HB2 datagram format.....	53
Simrad HFB	
datagram format.....	54
Simrad HFB datagram format.....	54
Simrad MDS	
datagram format.....	60
Simrad MTW	
datagram format.....	55
Simrad MTW datagram format .....	55
Simrad PSIMP,C	
datagram format.....	47
Simrad PSIMP,D	
datagram format.....	49
Simrad PSIMP,D datagram format .....	47, 49
Simrad PSIMP,F	
datagram format.....	51
Simrad PSIMP,F datagram format.....	51
Simrad TDS	
datagram format.....	55
Simrad TDS datagram format.....	55
Simrad TFI	
datagram format.....	56
Simrad TFI datagram format.....	56
Simrad TPC	
datagram format.....	56
Simrad TPC datagram format.....	56
Simrad TPR	
datagram format.....	57
Simrad TPR datagram format.....	57
Simrad TPT	
datagram format.....	58
Simrad TPT datagram format.....	58
Simrad TS2	
datagram format.....	59
Simrad TS2 datagram format .....	59
Simrad TTS	
datagram format.....	59
Simrad TTS datagram format .....	59
software license	
about .....	7
software version	
about .....	7
sound speed	
datagram formats .....	18
speed log	
datagram formats .....	19
Standard NMEA 0183 communication	
parameters.....	27
support	
information .....	9
offices.....	9
Support information .....	9
Supported datagram formats for annotation	
data .....	13
Supported datagram formats for catch monitoring	
information .....	18
Supported datagram formats for external depth	
input .....	14
Supported datagram formats for external	
objects.....	21
Supported datagram formats for GPS (position)	
information .....	14
Supported datagram formats for heading and gyro	
information .....	15
Supported datagram formats for motion	
information .....	22
Supported datagram formats for palette control .....	21
Supported datagram formats for sound speed	
sensors .....	18
Supported datagram formats for speed log	
information .....	19
Supported datagram formats for target marker	
outputs .....	23
Supported datagram formats for temperature	
information .....	20

---

Supported datagram formats for trawl information.....	16	datagram format.....	43
Supported datagram formats for wind information.....	20	VWR datagram format.....	44
SW software version.....	7		
SW license about.....	7		
<b>T</b>			
target audience this publication.....	7	website document downloads.....	7
target markers datagram formats .....	23	online information.....	7
TDS datagram format.....	55	wind direction datagram formats .....	20
technical support information .....	9	wind speed datagram formats .....	20
offices.....	9		
Teledyne TSS1 datagram format .....	72		
temperature datagram formats .....	20		
TFI datagram format.....	56		
this publication about.....	7		
purpose .....	7		
target audience .....	7		
this user manual about .....	7		
purpose .....	7		
target audience .....	7		
THS datagram format.....	40		
TLL datagram format.....	40		
TPC datagram format.....	56		
TPP (Tracked Target Position) datagram format.....	61		
description (datagram format).....	61		
TPR datagram format.....	57		
TPT datagram format.....	58		
trawl information datagram formats .....	16		
Trimble PTNL,GGK datagram format.....	69		
Trimble PTNL,GGK datagram format.....	69		
TS2 datagram format.....	59		
TSS1 datagram format.....	72		
TTS datagram format.....	59		
<b>V</b>			
VBW datagram format.....	41		
VHW datagram format.....	42		
VTG			

©2023 Kongsberg Maritime

ISBN 978-82-8066-239-2





KONGSBERG

KONGSBERG MARITIME  
SIMRAD  
Strandpromenaden 50  
P.O.Box 111  
[kongsberg.com/simrad](http://kongsberg.com/simrad)

Switchboard: +47 815 73 700  
E-mail sales: [simrad.sales@simrad.com](mailto:simrad.sales@simrad.com)  
E-mail support: [simrad.support@simrad.com](mailto:simrad.support@simrad.com)



[kongsberg.com/simrad](http://kongsberg.com/simrad)